
PRODUCT DATA SHEET PRODUCT CODE: AW00004

Kardo System - 1127mm - 3000K - Black - Undimmable




DESIGN BY

Paolo Mantero, Jacopo Acciaro

DESCRIPTION

Kardo is a suspension lamp office capable of providing at the same time a general lighting and personal. The ambient lighting is mainly diffused indirect, direct emission is controlled by a micro-prism methacrylate lower diffuser in transparent with UGR <19 and lets achieve a 300lux illuminance on the work surface. This is activated / deactivated by means of two presence detectors and is controlled by a daylight sensor placed in the end caps. The device is therefore designed to provide independently for on, off and the primary light intensity adjustment. When workstations are abandoned, the primary light initially maintains the previous state and then lower its intensity and off according to predetermined time intervals. Whenever the unit detects a new presence of people, the primary light is turned back with proper intensity to daylight In the central part of the device you can be activated two task light. Kardo is in fact designed to meet the needs of offices, in particular to manage the light in configurations with frontally positioned desks. The task light are focused on the work area, create a illuminance useful contribution to achieve 500 lux and can be managed directly by the user. The switching on and off of the personal light takes place in fact through proximity sensor. Auto Power Off is synchronized to switching off the general light in the absence of personnel in the work. Kardo do not only ensures correct performance of light but intelligent user interaction. It allows the customization of your area in compliance with regulations and manage independently the general illumination according to the real needs of presence and natural light to ensure functionality and energy saving.

TECHNICAL DRAWINGS



FEATURES

Article Code: Colour: Installation: Environment:	AW00004 White Suspension Indoor	Material: Series: Emission:	Structural elements in extruded aluminum and end caps in ABS. Upper diffuser in satin opal methacrylate. Lower diffuser made of transparent methacrylate micro prism. Indoor Direct/indirect
DIMENSIONS			

Length: cm 113 Width: cm 25 Height: cm 5

INCLUDED SOURCES

LED Category: Color temperature (K): Number: CRI: Watt: 56W Delivered lumens output (Im): 4843lm Λ

Type: Class: Α

LUMINAIRE

Watt: 56W Delivered lumens output (lm): 4843lm CCT: 3000K CRI:

80

3000K

80



PRODUCT DATA SHEET

ACCESSORIES

NO IMAGE AVAILABLE

End Caps -Without Sensor -Black AW00804

> NO IMAGE AVAILABLE

Direct Emission Screens - 2247mm AW05400

NO IMAGE AVAILABLE

Direct Emission Screens -50.000mm AW05700 NO IMAGE AVAILABLE

End Caps - With Sensor - Black AW00904

NO IMAGE AVAILABLE

Direct Emission Screens -10.000mm AW05500

> NO IMAGE AVAILABLE

Intermediate Suspension Kit (x1) AW05000 NO IMAGE AVAILABLE

Direct Emission Screens - 1127mm AW05300

> NO IMAGE AVAILABLE

Direct Emission Screens -25.000mm AW05600

> NO IMAGE AVAILABLE

End Suspension Kit (x1) AW05100