

Label Light - Double connection - 8W 2900K



IP65 ♠ ▼


DESIGN BY

Studio Artemide

DESCRIPTION

Light fixture with 5mm LED light sources. Wall and ceiling installation by means of special accessories (clips). 26mm-diameter body in UV-stabilized transparent polycarbonate. Pre-resined PVC stoppers with oring. PVC clips for fixing and adjustment (standard supply).

TECHNICAL DRAWINGS



EFATLIRES

Article Code: Installation:	Al10000 Wall, Ceiling	Material:	Transparent polycarbonate
mstanation.	vvaii, Ceiiiiig	Series:	Outdoor
DIMENSIONS			
Length:	cm 85		
Width:	cm 3.6		
Height:	cm 3.6		
Weight:	kg 0.3		
INCLUDED SOURCES			
Category:	LED	Color temperature (K):	2900K
Number:	1	CRI:	= 80
Nullibel.			
	8W		
Watt: Type:	8W 0		

 Trasformer availability:
 Single-phase transformer external safety
 Delivered lumens output (lm): 285lm

 CCT:
 2900K

 57%

 Watt:
 8W
 Efficacy:
 35.67lm/W

 CRI:
 80

Notes

Electrical connection to the mains by means of transformer.



PRODUCT DATA SHEET

ACCESSORIES

NO IMAGE AVAILABLE

DRIVER 25W 24V DC T409996

NO IMAGE AVAILABLE

Wall fixing Al90000 NO IMAGE AVAILABLE

DRIVER 90W 24V DC T409999

> NO IMAGE AVAILABLE

Mini IP68 terminal block NL18274 NO IMAGE AVAILABLE

Driver cv 150W 24Vdc DV5004

> NO IMAGE AVAILABLE

DRIVER 60W 24V DC T409998