

LineaLed Wallwasher 25W - 28° 3000K



IP65/67 💮 😿

TECHNICAL DRAWINGS

00000000000000	a 47,5
300/500/780/978	65

DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

Walk-over and drive-over recessed floor installation.Composed by body in extruded aluminium,protection glass; provided with junction box for input/output connection.Body fastened to the recessing box by means of proper pre-stressed steel springs supplied with the fixture.

24Vdc remote ballast.

Connect a maximum number of 3 fixtures in a continuous line.

Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions.

Article Code: Colour: Installation:	NL1732225K0 Silver gray Recessed	Material: Series: Area contract:	Aluminium,transpare tempered glass. Outdoor Outdoor
DIMENSIONS			
Length: Width: Height: Weight:	cm 78 cm 4.8 cm 9 kg 2.2	Impact Resistance:	IK07
INCLUDED SOURCI	S		
Category: Number: Watt: Delivered lumens outp Type: Class:	LED 3 8,5W ut (Im): 1776Im 0 A	Color temperature (K): Voltage:	3000K 24Vdc
LUMINAIRE			
Power Supply: Watt: Voltage:	Elettronic 25W 24 Vdc	Delivered lumens output (l CCT: CRI:	l m): 1234lm 3000K 80
Notes			

Medium luminous flux to highlight details, large sections of windows.(25° optic)



ACCESSORIES

