





IP65/67 💮 😿

## **TECHNICAL DRAWINGS**

<u>○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○</u> 300/500/780/978	47,5 

## **DESIGN BY**

Carlotta de Bevilacqua

## DESCRIPTION

Walk-over and drive-over recessed floor installation.Composed by body in extruded aluminium,protection glass; provided with junction box for input/output connection.Body fastened to the recessing box by means of proper pre-stressed steel springs supplied with the fixture.

24Vdc remote ballast.

Connect a maximum number of 10 fixtures in a continuous line.

Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions.

FEATURES				
Article Code: Colour:	NL17320ELK0 Silver gray	Material:	Aluminium,transparer tempered glass.	
Installation:	Recessed	Series:	Outdoor	
		Area contract:	Outdoor	
DIMENSIONS				
Length:	cm 30	Impact Resistance:	IK07	
Width:	cm 4.8			
Height:	cm 9			
Weight:	kg 0.9			
INCLUDED SOURCES				
Category:	LED	Color temperature (K):	3000K	
Number:	1	Voltage:	24Vdc	
Watt:	8,5W			
Delivered lumens output (lm): 1776lm				
Туре:	0			
Class:	A			
LUMINAIRE				
Power Supply:	Elettronic	Delivered lumens output (lm): 416lm		
Watt:	8,5W	CCT:	3000K	
Voltage:	24 Vdc	CRI:	80	
Notes				
Flood optic				

Wide luminous flow suitable for lighting large areas.(40° optic)



## ACCESSORIES

