


PRODUCT DATA SHEET

Luceri LED Kadro Trimless - Faceted Mirror Optics 4000K - Driver 35W DALI



IP20/44 without screen - 20/54 with screen






DESIGN BY

Studio Artemide

DESCRIPTION

Luceri LED and Kadro LED offer a modular range of professional downlighters, highly flexible, providing customisable lighting solutions for every need. Thanks to TrueWhite technology, colour temperature and colour rendering index are maintained constant throughout the lifespan of this product, guaranteeing a consistent light quality. The emission of versions with metal reflector is compliant with EN12464 and has UGR<19, producing an effective and comfortable lighting solution.

TECHNICAL DRAWINGS



FEATURES

Article Code: Installation:	BB11100 DV1018 Recessed, Ceiling	Material: Series: Area contract:	Bezel, white reflector and screens in polycarbonate, reflectors in vacuum- metalled polycarbonate with anti-scratch surface treatment. Indoor Hospitality, null, Office
DIMENSIONS			
Length: Width: Height: Weight:	cm 31.8 cm 19.5 cm 19.5 kg 1.7	Cutout Width: Cutout length: Cutout shape:	cm 19.5 cm 19.5 Squared
INCLUDED SOURCES			
Category: Number: Watt: Type:	LED 1 max 54W 0	Color temperature (K): CRI:	4000K 90
LUMINAIRE			
Trasformer availability: Watt:	35W 27W	Delivered lumens output (lm) CCT: Efficiency: Efficacy: CRI: Dimmable Typology:	: 2695lm 4000K 81% 99.83lm/W 90
Notes			

Driver 220/240Vac 50/60Hz supplied separately. To be completed with recessed frame.



PRODUCT DATA SHEET

ACCESSORIES



Accessory fo ceiling installation M239920



Transparent screen in polycarbonate M239300



Prismoptic screen in polycarbonate M239500



Sharp edge trim M240700



Opal screen in PMMA M239400



Support with rounded edge trim M240800