750°C

3000K

PRODUCT DATA SHEET

Null Vector Beta - White



IP20 ☐ Dimmerable: +**①**-


DESIGN BY

Carlotta de Bevilacqua, Laura Pessoni

DESCRIPTION

Null Vector displays a full combination of optical and mechanical performance. The aluminium body is both a structural and an optical component for light emission control. The whole structure is generated from an escalating growth of an individual punching and cutting mould, designed in the two versions alfa and beta. This matrix is characterized by a punch pattern with three functions - luminous, perceptive, and mechanical. While, on one hand, it is the result of a well-calculated study of light emission in space, translated into a graphic element supporting perception, on the other it derives from surpassing the limits of the material's processing technology. The optical system with an energy-saving light source with E14 connection also includes a texturized glazed diffuser, which ensures uniform lighting. The multi-faceted punched structure generates a magic lighting effect evoking the product's simplicity and lightweight in all the available finishes.

TECHNICAL DRAWINGS



FEATURES

Article Code:		Material:	Aluminium,
Colour:	White		methacrylate
Installation:	Suspension	Series:	Scenarios

Glow Wire Test:

Color temperature (K):

DIMENSIONS

Length:	cm 13.7
Height:	cm 15
Depth:	cm 13.7
Max Height from ceiling:	cm 200

SOURCES NOT INCLUDED

Category:	LED
Number:	1
Watt:	6W
Type:	2
Socket:	E14
Class:	Α

LUMINAIRE

Watt:	6W	Delivered lumens of	Delivered lumens output (lm):390lm	
Voltage:	230V	CCT:	3000K	
		Efficacy:	55,7lm/W	