


Pad 80 fixed diffuser - Gloss anodized - 9,5W 4000K - 98°



IP44 🔔

TECHNICAL DRAWINGS



DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

Efficient, clear accent lighting, fixed and adjustable. Diffused ambient lighting (in fixed version). 2 colour temperatures: warm white (3000K) and neutral white (4000K) - CRI=80 (min.). Excellent lighting efficiency > 70lm/W. High adjustability: 360° rotation, +90°/-90° tilt angle. Fixed version available as IP44. Easy installation of light modules, no tools required. Lighting units available in 3 finishes: gloss aluminium, painted white, painted black. Structural elements of recessed-mounted version available in 3 sizes, for use with 1, 2, 3 and 2x2 modules. 3 compatible finishes (polished aluminium, white, and black). Housing of ceiling-mounted version available in 3 sizes (1, 2, 3 lighting units), and 3 compatible finishes (polished aluminium, white and black). Recessed-mounted version available as trimless or framed. Materials: body in anodized extruded aluminium, diffuser in opal polycarbonate. Complies with standard EN60598-1 and other specific standards.

	10045360	. ·	
Article Code: Colour:	M245760 Gloss anodized	Series: Area contract:	Indoor
			Hospitality, null,
Installation:	Projector, Recessed	1	Retail, Culture
DIMENSIONS			
Length:	cm 8	Cutout shape:	Squared
Width:	cm 8	Glow Wire Test:	650
Height:	cm 2	Hole in false ceiling:	80x80 mm
Weight:	kg 0.3		
Recessed depth:	cm 5.5		
INCLUDED SOURC	ES		
Category:	LED	Color temperature (K):	4000K
Number:	1	Color Tolerance:	MacAdam 4SDCN
Watt:	9W	CRI:	=80 (min.)
Delivered lumens output (lm):911lm		Efficacy:	101lm/W
Туре:	0	Service Life:	L70(6K) > 60500h
Class:	А		
LUMINAIRE			
Watt:	9.5W	Delivered lumens output (lm):705lm	
Voltage:	12V	CCT:	4000K
		Efficiency:	100%
		Efficacy:	74.16lm/W
		CRI:	80

Notes

LED 9W 2x61° 4000K