


Pad 80 With fixed lenses - White - 9,5W 3000K - 12°



IP44 🕘

TECHNICAL DRAWINGS



DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

Efficient, clear accent lighting, fixed and adjustable. Diffused ambient lighting (in fixed version). 2 colour temperatures: warm white (3000K) and neutral white (4000K) - CRI=80 (min.). Excellent lighting efficiency > 70lm/W. High adjustability: 360° rotation, +90°/-90° tilt angle.Fixed version available as IP44. Easy installation of light modules, no tools required. Lighting units available in 3 finishes: gloss aluminium, painted white, painted black. Structural elements of recessed-mounted version available in 3 sizes, for use with 1, 2, 3 and 2x2 modules. 3 compatible finishes (polished aluminium, white, and black). Housing of ceiling-mounted version available in 3 sizes (1, 2, 3 lighting units), and 3 compatible finishes (polished aluminium, white and black).Recessed-mounted version available as trimless or framed. Materials: body in anodized extruded aluminium, diffuser in opal polycarbonate.Complies with standard EN60598-1 and other specific standards.

FEATURES				
Article Code:	M245020	Series:	Indoor	
Colour:	White	Area contract:	Hospitality, null,	
Installation:	Projector, Rece	ssed	Retail, Culture	
DIMENSIONS				
Length:	cm 8	Glow Wire Test:	650	
Width:	cm 8			
Height:	cm 2.5			
Weight:	kg 0.3			
INCLUDED SOURC	ES			
Category:	LED	Color temperature (K):	3000K	
Number:	1	Color Tolerance:	MacAdam 4SDCM	
Watt:	9W	CRI:	=80 (min.)	
Delivered lumens output (lm):851lm		Efficacy:	95lm/W	
Туре:	0	Service Life:	L70(6K) > 60500h	
Class:	A			
LUMINAIRE				
Watt:	9.5W	Delivered lumens output	Delivered lumens output (lm):710lm	
Voltage:	12V	CCT:	3000K	
		Efficiency:	100%	
		Efficacy:	74.74lm/W	
		CRI:	0	

Notes

LED 9W 2x6° 3000K