


Picto 100 LED track vertical - white 63° 3000K - Eutrac - Not Dimmable



IP20 🔔 ce

TECHNICAL DRAWINGS



DESIGN BY

Studio Artemide

DESCRIPTION

This range of professional projectors is distinguished by design, excellent performance and flexibility. Picto is a complete and versatile range, suitable for use in retail spaces, showrooms, museums or art galleries. Available in 3 sizes, installation options, designs, colours, optics and a wide range of accessories.

Article Code:AD10301Material:aluminiumColour:WhiteSeries:IndoorInstallation:Projector, Track, CeilingArea contract:Hospitality, Retail, CultureEnvironment:IndoorArea contract:Hospitality, Retail, CultureDIMENSIONSIndoorCultureLength:cm 15.4Glow Wire Test:850Height:cm 22.1Kg 2.6Inclination:-90+90Rotation:cm 355Color temperature (K):3000KNumber:1Color Tolerance:MacAdam 2SDCMVatt:35WService Life:L70 (6K) 50000hType:0Class:ALUMINAIREPower Supply:Power supply 220/240Vac 50/60HzDelivered lumens output (lm): 2836lm 2000KWatt:35WEfficiency:81%Watt:35WEfficiency:81%	FEATURES			
Colour:White Projector, Track, CeilingSeries:IndoorInstallation:Projector, Track, CeilingArea contract:Hospitality, Retail, CultureEnvironment:IndoorArea contract:Hospitality, Retail, CultureDIMENSIONSIndoorSeries:SolutureLength:cm 15.4 (g 2.6)Glow Wire Test:850Height:cm 22.1 (g 2.6)Weight:kg 2.6 (g 2.6)Inclination:-90+90 (m 355)SolutureSolutureINCLUDED SOURCESColor temperature (K):3000K (MacAdam 2SDCM)Number:1Color Tolerance:MacAdam 2SDCM) (K) 50000hNumber:1Color Tolerance:L70 (6K) 50000hType:0Service Life:L70 (6K) 5000hClass:AService Life:2300KLUMINAIREPower Supply:Power supply (220/240Vac 50/6Hz)Selivered lumens output (Im: 2836Im) CCT:Watt:35WEfficiency:81%		1010201	Mataila	- Louis for Louis
Installation:Projector, Track, Ceiling IndoorArea contract:Hospitality, Retail, CultureDIMENSIONSIndoorIndoorIndoorDIMENSIONScm 15.4Glow Wire Test:850Length:cm 22.1Kg 2.6Inclination:Hospitality, Retail, Culturecm 22.1SolorWeight:kg 2.6Inclination:-90+90Rotation:cm 355SolorSolorINCLUDED SOURCESColor temperature (K):3000KCategory:LEDColor Tolerance:MacAdam 2SDCMNumber:1Color Tolerance:MacAdam 2SDCMYatt:35WService Life:L70 (6K) 50000hType:0Class:ALUMINAIREPower supply 220/240Vac 50/60Hz includedDelivered lumens output (Im): 2836Im 220/240Vac 50/60Hz Efficiency:81%Watt:35WEfficiency:81%				
CeilingCeilingCultureEnvironment:IndoorCultureDIMENSIONSSolutionSolutionLength:cm 15.4Glow Wire Test:850Height:cm 22.1Wire Test:850Weight:kg 2.6Inclination:-90+90Rotation:cm 355SolutionSolutionINCLUDED SOURCESColor temperature (K):3000KNumber:1Color Tolerance:MacAdam 2SDCMWatt:35WService Life:L70 (6K) 50000hType:0Color Tolerance:MacAdam 2SDCMLUMINAIREPower supply:Delivered lumens output (Im): 2836ImPower Supply:Power supplyDelivered lumens output (Im): 2836ImWatt:35WEfficiency:81%Watt:35WEfficiency:81%				
Environment: Indoor DIMENSIONS Length: cm 15.4 Glow Wire Test: 850 Height: cm 22.1 Weight: kg 2.6 Inclination: -90+90 Rotation: cm 355 INCLUDED SOURCES Category: LED Color temperature (K): 3000K Number: 1 Color Tolerance: MacAdam 2SDCM Watt: 35W Service Life: L70 (6K) 50000h Type: 0 Class: A LUMINAIRE Power Supply: Power supply 220/240Vac 50/60Hz CCT: 3000K LUMINAIRE Power Supply: Power supply 220/240Vac 50/60Hz CCT: 3000K Efficiency: 81% Watt: 35W Efficacy: 81%	Installation:		Area contract:	
DIMENSIONSLength:cm 15.4Glow Wire Test:850Height:cm 22.1Weight:kg 2.6Inclination:-90+90Actation:SourceRotation:cm 355Color temperature (K):3000KINCLUDED SOURCESColor Tolerance:MacAdam 2SDCMCategory:LEDColor Tolerance:MacAdam 2SDCMNumber:1Color Tolerance:MacAdam 2SDCMVatt:35WService Life:L70 (6K) 50000hType:0Color Tolerance:MacAdam 2SDCMLUMINAIREPower Supply:Power supplyDelivered lumens output (Im): 2836ImPower Supply:Power supplyDelivered lumens output (Im): 2836ImincludedEfficiency:81%Watt:35WEfficiency:81%		0		Culture
Length:cm 15.4Glow Wire Test:850Height:cm 22.1kg 2.6inclination:-90+90Rotation:-90+90cm 355inclination:-90+90Rotation:cm 355inclination:-90+90Rotation:cm 355inclination:3000KINCLUDED SOURCEScolor temperature (K):3000KNumber:1Color Tolerance:MacAdam 2SDCMVatt:35WService Life:L70 (6K) 50000hType:0class:ALUMINAIREPower supplyDelivered lumens output (Im): 2836lmPower Supply:Power supply includedCCT:3000KWatt:35WEfficiency:81%	Environment:	Indoor		
Initiation:Color functionWeight:kg 2.6Inclination:-90+90Rotation:cm 355INCLUDED SOURCESCategory:LEDCategory:LED1Color temperature (K):35WService Life:Vatt:35WService Life:L70 (6K) 50000hType:0Class:ALUMINAIREPower Supply:Power supply 220/240Vac 50/60Hz includedPowert:35WEfficiency:81%Watt:35WStringBillionColor Tolerance:MacAdam 2SDCMLUMINAIREFfficiency:BookService Life:StringStringPower Supply:Power supply 20/240Vac 50/60HzBookEfficiency:81%81.02lm/W	DIMENSIONS			
Weight:kg 2.6Inclination:-90+90Rotation:cm 355INCLUDED SOURCESColor temperature (K):3000KCategory:LEDColor Tolerance:MacAdam 2SDCMNumber:1Color Tolerance:MacAdam 2SDCMWatt:35WService Life:L70 (6K) 50000hType:0Class:ALUMINAIREPower supply:Delivered lumens output (Im): 2836ImPower Supply:Power supplyDelivered lumens output (Im): 2836ImMatt:35WEfficiency:81%Watt:35WEfficiency:81.02Im/W	Length:	cm 15.4	Glow Wire Test:	850
Inclination:-90+90 Rotation:-90+90 Rotation:Rotation:cm 355INCLUDED SOURCESLEDColor temperature (K):3000KNumber:1Color Tolerance:MacAdam 2SDCMWatt:35WService Life:L70 (6K) 50000hType:0Class:ALUMINAIREPower supply:Delivered lumens output (Im): 2836Im 220/240Vac 50/60HzService Life:3000KWatt:35WBelivered lumens output (Im): 2836Im CCT:Sanot 3000KWatt:35WEfficiency:81%	Height:	cm 22.1		
Rotation:cm 355INCLUDED SOURCESColor temperature (K):3000KCategory:LEDColor Tolerance:MacAdam 2SDCMNumber:1Color Tolerance:MacAdam 2SDCMWatt:35WService Life:L70 (6K) 50000hType:0Class:ALUMINAIREPower supplyDelivered lumens output (Im): 2836ImPower Supply:Power supplyDelivered lumens output (Im): 2836ImMatt:35WEfficiency:81%Watt:35WEfficacy:81.02Im/W	Weight:	kg 2.6		
INCLUDED SOURCESCategory:LEDColor temperature (K):3000KNumber:1Color Tolerance:MacAdam 2SDCMWatt:35WService Life:L70 (6K) 50000hType:0Service Life:L70 (6K) 50000hClass:AAEumerature (Immediate Constraints)Power Supply:Power supply 220/240Vac 50/60Hz includedDelivered lumens output (Im): 2836Im 200KWatt:35WEfficiency:81%	Inclination:	-90+90		
Category: LED Color temperature (K): 3000K Number: 1 Color Tolerance: MacAdam 2SDCM Watt: 35W Service Life: L70 (6K) 50000h Type: 0 Class: A LUMINAIRE Power supply: Power supply Delivered lumens output (Im): 2836Im 220/240Vac 50/60Hz CCT: 3000K included Efficiency: 81% Watt: 35W Efficacy: 81.02Im/W	Rotation:	cm 355		
Number:1Color Tolerance:MacAdam 2SDCMWatt:35WService Life:L70 (6K) 50000hType:0Class:ALUMINAIREPower Supply:Power supply 220/240Vac 50/60Hz includedDelivered lumens output (Im): 2836Im CCT:2836Im 3000K Efficiency:Watt:35WEfficiency:81%	INCLUDED SOURCES			
Number:1Color Tolerance:MacAdam 2SDCMWatt:35WService Life:L70 (6K) 50000hType:0Service Life:L70 (6K) 50000hClass:AAService Life:L70 (6K) 50000hLUMINAIREPower Supply:Power supply 220/240Vac 50/60Hz includedDelivered lumens output (Im): 2836Im 200K Efficiency:Watt:35WEfficiency:81%	Category:	LED	Color temperature (K):	3000K
Type: 0 Class: A LUMINAIRE Power supply Delivered lumens output (lm): 2836lm 220/240Vac 50/60Hz CCT: 3000K included Efficiency: 81% Watt: 35W Efficacy: 81.02lm/W	• •	1	Color Tolerance:	MacAdam 2SDCM
Type: Class: 0 LUMINAIRE Power supply Delivered lumens output (lm): 2836lm 220/240Vac 50/60Hz included CCT: 3000K Efficiency: 81% Watt: 35W Efficacy: 81.02lm/W	Watt:	35W	Service Life:	L70 (6K) 50000h
Class: A LUMINAIRE Power Supply: Power supply 220/240Vac 50/60Hz included Delivered lumens output (Im): 2836Im CCT: 3000K Efficiency: 81% Watt: 35W Efficacy: 81.02Im/W	Type:	0		. ,
Power Supply: Power supply Delivered lumens output (lm): 2836lm 220/240Vac 50/60Hz CCT: 3000K included Efficiency: 81% Watt: 35W Efficacy: 81.02lm/W		A		
220/240Vac 50/60Hz CCT: 3000K included Efficiency: 81% Watt: 35W Efficacy: 81.02lm/W	LUMINAIRE			
220/240Vac 50/60Hz CCT: 3000K included Efficiency: 81% Watt: 35W Efficacy: 81.02lm/W	Power Supply:	Power supply	Delivered lumens output (lm)	: 2836lm
included Efficiency: 81% Watt: 35W Efficacy: 81.02lm/W		11.5		
Watt: 35W Efficacy: 81.02lm/W		220/2 10100 00/00/12		
	Watt:		•	
		5511	CRI:	90



ACCESSORIES



PICTO 100 -Accessory-holder + Louvre (black). Black M081737



PICTO 100 -Accessory-holder (black) + Adjustable dowser (black) M082637



Accessory for ceiling installation (white) L176320



PICTO 100 - U Filter. M080545



PICTO 100 -Accessory-holder + wall washer screen (black). Black M082737