


PRODUCT DATA SHEET

Picto 70 LED track vertical - white 14° 3000K - Dali



TECHNICAL DRAWINGS



DESIGN BY

Studio Artemide

DESCRIPTION

This range of professional projectors is distinguished by design, excellent performance and flexibility. Picto is a complete and versatile range, suitable for use in retail spaces, showrooms, museums or art galleries. Available in 3 sizes, installation options, designs, colours, optics and a wide range of accessories.

Article Code:AD03701Material:aluminumColour:WhiteSeries:IndoorInstallation:Projector, Track, CeilingArea contract:Hospitality, Retail, CultureEnvironment:IndoorArea contract:Hospitality, Retail, CultureDIMENSIONSIndoorIndoorLength:cm 7.8 (m 21.5)Glow Wire Test:850Weight:kg 1.2Inclination: -90+90-90+90Rotation:cm 355Color temperature (K): Color Tolerance:3000 K MacAdam 2SDCMNumber:1Color Tolerance: Service Life:MacAdam 2SDCM Life L70 (6K) 50000hType:0Class:ALUMINAIREPower supply 220/240Vac 50/60Hz includedDelivered lumens output (Im): 1095Im CCT:3000 K MoorkWatt:20WEfficiency: 69% GRI:69% GRI:90	FEATURES			
Colour: Installation:White Projector, Track, CeilingSeries: Area contract:IndoorInstallation:Projector, Track, CeilingArea contract:Hospitality, Retail, CultureEnvironment:IndoorArea contract:Hospitality, Retail, CultureDIMENSIONSIndoorIndoorLength:cm 7.8 (m 21.5)Glow Wire Test:850Height:cm 21.5 (weight:kg 1.2 (m 355)Solon KInclination:-90+90 (m 355)Color temperature (K):3000 KINCLUDED SOURCESColor Tolerance:MacAdam 2SDCMInduct:20 WService Life:Life L70 (6K) 50000hType:0 Class:ADelivered lumens output (Im: 1095Im 220/240Vac 50/60HzPower Supply:Power supply 220/240Vac 50/60HzDelivered lumens output (Im: 1095Im CCT:3000K 69%Watt:20 WEfficency:69%Watt:20WEfficacy:54.76Im/W		AD03701	Material [.]	aluminum
Installation:Projector, Track, CeilingArea contract:Hospitality, Retail, CultureEnvironment:IndoorArea contract:Hospitality, Retail, CultureDIMENSIONSIndoorIndoorIndoorDIMENSIONSIndianaSooSooLength:cm 7.8 (g 1.2)Glow Wire Test:850Height:cm 21.5 (g 1.2)Kg 1.2 (Inclination: cm 355SooINCLUDED SOURCEScolor temperature (K): (Color Tolerance: MacAdam 2SDCM3000 K (MacAdam 2SDCM)Number:1 20 WService Life:Life L70 (6K) 50000hType:0 Class:AService Life:Life L70 (6K) 50000hLUMINAIREPower Supply: 220/240/ac 50/60Hz includedDelivered lumens output (Im: 1095Im 200K3000 K GCT: 69%Watt:20 WEfficiency: Efficiency:69% 69%				
InternationProjection (noise) CeilingInternationPropriation (noise) CultureEnvironment:IndoorCultureDIMENSIONSGlow Wire Test:850Length: Height:cm 7.8 (m 21.5)Glow Wire Test:850Weight: Metation:kg 1.2 (noise)SourceSourceInclination: Number:-90+90 (m 355)Glow Wire Test:850INCLUDED SOURCESColor temperature (K): (Color Tolerance:3000 K MacAdam 2SDCMNumber: Watt:1 20 WColor Tolerance: Service Life:MacAdam 2SDCM Life L70 (6K) 50000hLUMINAIREPower supply 220/240Vac 50/60Hz includedDelivered lumens output (Im): 1095Im 220/240Vac 50/60HzPower Supply:Power supply 220/240Vac 50/60HzDelivered lumens output (Im): 1095Im Efficiency:69% 69%Watt:20WEfficiency: Efficiency:69% 54.76Im/W				
Environment:IndoorDIMENSIONSGlow Wire Test:850Length:cm 7.8 cm 21.5 Weight:Glow Wire Test:850Height:cm 21.5 kg 1.2 Inclination:-90+90 court 355Sold Wire Test:850INCLUDED SOURCESColor temperature (K):3000 KINCLUDED SOURCESColor Tolerance:MacAdam 2SDCMNumber:1Color Tolerance:MacAdam 2SDCMWatt:20 WService Life:Life L70 (6K) 50000hType:0Color Tolerance:Jife L70 (6K) 50000hClass:ADelivered lumens output (Im):1095ImPower Supply:Power supply 200/240Vac 50/60Hz includedDelivered lumens output (Im):1095ImWatt:20WEfficiency:69%Watt:20WEfficiency:69%	instantion			
Length:cm 7.8 cm 21.5 kg 1.2 Inclination:Glow Wire Test:850Weight:kg 1.2 -90+90 cm 355inclination:-90+90 cm 355inclination:90+90 cm 355INCLUDED SOURCESColor temperature (K):3000 K MacAdam 2SDCM MacAdam 2SDCM Service Life:3000 K Life L70 (6K) 50000h class:Matt:20 WService Life:Life L70 (6K) 50000h class:LUMINAIREPower supply 220/240Vac 50/60Hz includedDelivered lumens output (Im): 1095Im cCT:1095Im 3000K cH7Watt:20WEfficiency:69% 69%	Environment:	0		calcale
Length:cm 7.8 cm 21.5 kg 1.2 lnclination:Glow Wire Test:850Weight:kg 1.2 -90+90 cm 355inclination:-90+90 cm 355inclination:90+90 cm 355INCLUDED SOURCESColor temperature (K):3000 K MacAdam 2SDCMCategory:LED 1Color Tolerance:MacAdam 2SDCM MacAdam 2SDCMNumber:1Color Tolerance:MacAdam 2SDCM Life L70 (6K) 50000hWatt:20 W 0 Class:Service Life:Life L70 (6K) 50000h cm 220/240Vac 50/60Hz includedPower Supply:Power supply 220/240Vac 50/60Hz includedDelivered lumens output (Im): 1095Im CCT:1095Im 3000K conkWatt:20WEfficiency:69% 69%				
InitialContributionSocialHeight:cm 21.5kg 1.2Inclination:-90+90Rotation:cm 355INCLUDED SOURCESCategory:LEDCategory:LED1Color Tolerance:MacAdam 2SDCMWatt:20 W20 WService Life:LIMINAIREPower Supply:Power supply220/240Vac 50/60HzCCT:3000KincludedEfficiency:69%Watt:20W20WEfficacy:54.76lm/W	DIMENSIONS			
Weight:kg 1.2Inclination:-90+90Rotation:cm 355INCLUDED SOURCESColor temperature (K):3000 KCategory:LEDColor Tolerance:MacAdam 2SDCMNumber:1Color Tolerance:MacAdam 2SDCMWatt:20 WService Life:Life L70 (6K) 50000hType:0Calass:ALUMINAIREPower supply:Delivered lumens output (Im): 1095Im 220/240Vac 50/60HzCCT:3000KWatt:20WEfficiency:69%Watt:20WEfficiency:54.76Im/W	Length:	cm 7.8	Glow Wire Test:	850
Inclination:-90+90 cm 355Rotation:cm 355INCLUDED SOURCESLEDColor temperature (K):3000 KCategory:LEDColor Tolerance:MacAdam 2SDCMWatt:20 WService Life:Life L70 (6K) 50000hType:0Class:ALUMINAIREPower supply:Power supplyDelivered lumens output (Im): 1095Im 220/240Vac 50/60HzPower Supply:20WEfficiency:69% 69%Watt:20WEfficacy:54.76Im/W	Height:	cm 21.5		
Rotation:COUSTRotation:Cm 355INCLUDED SOURCESLEDColor temperature (K):3000 KCategory:LEDColor Tolerance:MacAdam 2SDCMNumber:1Color Tolerance:MacAdam 2SDCMWatt:20 WService Life:Life L70 (6K) 50000hType:0Class:ALUMINAIREPower supplyDelivered lumens output (Im): 1095ImPower Supply:Power supplyDelivered lumens output (Im): 1095ImMatt:20WEfficiency:69%Watt:20WEfficacy:54.76Im/W	Weight:	kg 1.2		
INCLUDED SOURCES Category: LED Color temperature (K): 3000 K Number: 1 Color Tolerance: MacAdam 2SDCM Watt: 20 W Service Life: Life L70 (6K) 50000h Type: 0 Service Life: Life L70 (6K) 50000h Class: A Delivered lumens output (Im): 1095Im Power Supply: Power supply Delivered lumens output (Im): 1095Im 220/240Vac 50/60Hz CCT: 3000K included Efficiency: 69% Watt: 20W Efficiacy: 54.76Im/W	Inclination:	-90+90		
Category: LED Color temperature (K): 3000 K Number: 1 Color Tolerance: MacAdam 2SDCM Watt: 20 W Service Life: Life L70 (6K) 50000h Type: 0 Class: A LUMINAIRE Power supply Delivered lumens output (Im): 1095Im 220/240Vac 50/60Hz CCT: 3000K included Efficiency: 69% Watt: 20W Efficacy: 54.76Im/W	Rotation:	cm 355		
Category: LED Color temperature (K): 3000 K Number: 1 Color Tolerance: MacAdam 2SDCM Watt: 20 W Service Life: Life L70 (6K) 50000h Type: 0 Class: A LUMINAIRE Power supply Delivered lumens output (Im): 1095Im 220/240Vac 50/60Hz CCT: 3000K included Efficiency: 69% Watt: 20W Efficiacy: 54.76Im/W				
Number:1Color Tolerance:MacAdam 2SDCMWatt:20 WService Life:Life L70 (6K) 50000hType:0Service Life:Life L70 (6K) 50000hClass:AAEnd of the service Life:LUMINAIREPower Supply:Power supply 220/240Vac 50/60Hz includedDelivered lumens output (Im): 1095Im CCT:CCT:3000K 69%Watt:20WEfficiency:69%	INCLUDED SOURCES			
Watt: 20 W Service Life: Life L70 (6K) 50000h Type: 0 0 Life: Life L70 (6K) 50000h Class: A Delivered Limens output (Im): 1095Im 220/240Vac 50/60Hz CCT: 3000K included Efficiency: 69% 69% 69% Watt: 20W Efficacy: 54.76Im/W	Category:	LED	Color temperature (K):	3000 K
Type: 0 Class: A LUMINAIRE Power Supply: Power supply 220/240Vac 50/60Hz included Delivered lumens output (lm): 1095lm GCT: 3000K Efficiency: 69% Watt: 20W Efficacy: 54.76lm/W	Number:	1	Color Tolerance:	MacAdam 2SDCM
Class: A LUMINAIRE Power Supply: Power supply 220/240Vac 50/60Hz included Delivered lumens output (Im): 1095Im CCT: 3000K Efficiency: 69% Watt: 20W Efficacy: 54.76Im/W	Watt:	20 W	Service Life:	Life L70 (6K) 50000h
LUMINAIRE Power Supply: Power supply Delivered lumens output (lm): 1095lm 220/240Vac 50/60Hz CCT: 3000K included Efficiency: 69% Watt: 20W Efficacy: 54.76lm/W	Туре:	0		
Power Supply: Power supply Delivered lumens output (lm): 1095lm 220/240Vac 50/60Hz CCT: 3000K included Efficiency: 69% Watt: 20W Efficacy: 54.76lm/W	Class:	А		
220/240Vac 50/60Hz CCT: 3000K included Efficiency: 69% Watt: 20W Efficacy: 54.76lm/W	LUMINAIRE			
220/240Vac 50/60Hz CCT: 3000K included Efficiency: 69% Watt: 20W Efficacy: 54.76lm/W	Power Supply:	Power supply	Delivered lumens output (lm)	: 1095lm
includedEfficiency:69%Watt:20WEfficacy:54.76lm/W		11.5		
Watt: 20W Efficacy: 54.76lm/W				
•	Watt:		•	
			•	90

Dimmable Typology:

Dali



PRODUCT CODE: AD03701

ACCESSORIES



Accessory-holder (nero) + projection lens and framing device M083937



Accessory-holder (black) + Projection lens for gobo. Customized gobo to be ordered separately M083837



(black) + Adjustable dowser (black) M082837



Accessory-holder (black) + wall washer screen (black) M083037



Accessory for ceiling installation (white) L176320