


Reeds IP67 Triple



IP67 


DESIGN BY

Klaus Begasse

DESCRIPTION

Floor light fixture with diffuse emission, with monochromatic LED light sources. Available with IP20 protection rating for indoors, IP67 and IP68 for outdoors. IP67 and IP68 versions are available in Single or Triple shape. Light is diffused through 7 PMMA rods with different heights to give the impression of a reed bed and which can be screwed to the base by means of AISI 316 stainless steel bushes. Part of the light is also diffused on the floor around the base. The base has an irregular shape, which has been designed to allow a «mosaic» connection with other light fixtures so as to create an elaborate composition as needed. Technical features in compliance with EN60598-1 (IP20, IP67) and section 2-18 (IP68). Consists of a base made up of a transparent polycarbonate casing installed between 2 AISI316 stainless steel plates fixed by means of AISI316 stainless steel screws. Water sealing is assured by a silicone gasket. The light fixture can be fastened to the floor by means of the holes in the lower plate. Technopolymer aesthetic cover. Complete with integrated ballast and supplied with a 1.5 m-long H05RN-F 2x1 cable provided with IP67 connector for the electrical connection to the mains suitable for 5-13.5mm diameter cables.

TECHNICAL DRAWINGS



FEATURES

Article Code:	T087700	Material:	Methacrylate, polycarbonate
Colour:	Anthracite grey	Series:	Outdoor
Installation:	Bollard, Floor		

DIMENSIONS

Length:	cm 42	Impact Resistance:	IK10
Width:	cm 42	Glow Wire Test:	750
Height:	cm 150		

INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K
Number:	3	CRI:	80
Watt:	9,5W		
Type:	0		
Class:	A		

LUMINAIRE

Watt:	28W	Delivered lumens output (lm):	237lm
Voltage:	220-240V	CCT:	3000K
		Efficiency:	12%
		Efficacy:	9lm/W
		CRI:	80

Notes

220/240Vac 50/60Hz electronic ballast included.