Indoor

3000K



PRODUCT DATA SHEET

Sharp SMD - 22W 34° 3000K Dimmable DALI White



DESIGN BY

Carlotta de Bevilacqua


DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

Series:

Color temperature (K):

TECHNICAL DRAWINGS



FEATURES

Article Code: AF47101 Colour: White Installation: Ceiling **Environment:** Indoor

DIMENSIONS

Length: cm 30 Width: cm 4.5 Height: cm 9

LED

INCLUDED SOURCES

Category: Number: 22W Watt: 0 Type: Class: Α

LUMINAIRE

Watt: 24W Delivered lumens output (lm): 1504lm 3000K CCT:

Efficiency: 71% 62.68lm/W Efficacy: 90 CRI: **Dimmable Typology:** Dali

Notes

Screen and CV SELV driver supplied separately.



ACCESSORIES



Screen 4x Black AF95204



Screen 4x White AF95201

NO IMAGE AVAILABLE

Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of \$ 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses.

AF06000