Indoor

4000K



PRODUCT DATA SHEET

Sharp SMD - 22W 34° 4000K Dimmable DALI Black



DESIGN BY


Carlotta de Bevilacqua

DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

Series:

TECHNICAL DRAWINGS



FEATURES

Article Code: AF47404
Colour: Black
Installation: Ceiling
Environment: Indoor

DIMENSIONS

 Length:
 cm 30

 Width:
 cm 4.5

 Height:
 cm 9

INCLUDED SOURCES

 Category:
 LED

 Number:
 1

 Watt:
 22W

 Type:
 0

 Class:
 A

LUMINAIRE

Watt: 24W Delivered lumens output (Im): 1610lm

 CCT:
 4000K

 Efficiency:
 71%

 Efficacy:
 67.09lm/W

 CRI:
 90

 Dimmable Typology:
 Dali

Color temperature (K):

Notes

Screen and CV SELV driver supplied separately.



PRODUCT DATA SHEET

ACCESSORIES



Screen 4x Black AF95204



Screen 4x White AF95201

NO IMAGE AVAILABLE

Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of \$ 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses.

AF06000