


PRODUCT DATA SHEET

Sharp SMD - 22W 54° 3000K White



ΙΡ20 💮 🕻

TECHNICAL DRAWINGS



DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

FEATURES			
Article Code: Colour: Installation: Environment:	AF46201 White Ceiling Indoor	Series:	Indoor
DIMENSIONS			
Length: Width: Height:	cm 30 cm 4.5 cm 9		
INCLUDED SOURCES	S		
Category: Number: Watt: Type: Class:	LED 1 22W 0 A	Color temperature (K):	3000K
LUMINAIRE			
Watt:	24W	Delivered lumens output (CCT: Efficiency: Efficacy: CRI:	l m): 1558lm 3000K 73% 64.91lm/W 90
Notes			

Notes

Screen and CV SELV driver supplied separately.



ACCESSORIES



AF95204





Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of S 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses. AF06000