
Indoor

3000K



PRODUCT DATA SHEET

Sharp SMD - 33W 34° 3000K Black



DESIGN BY


Carlotta de Bevilacqua

DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

Series:

TECHNICAL DRAWINGS



FEATURES

Article Code: AF81104 Colour: Black Installation: Ceiling **Environment:** Indoor

DIMENSIONS

Length: cm 44.8 Width: cm 4.5 Height: cm 9

INCLUDED SOURCES

LED Category: Number: 33W Watt: Type: 0 Class: Α

LUMINAIRE

Watt: 36W Delivered lumens output (lm): 2256lm 3000K CCT: Efficiency: 71% 62.68lm/W Efficacy:

Color temperature (K):

CRI: 90

Notes

Screen and CV SELV driver supplied separately.



ACCESSORIES



Screen 4x Black AF95204



Screen 4x White AF95201

NO IMAGE AVAILABLE

Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of \$ 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses.

AF06000