


Sharp SMD - 33W 34° 3000K Silver




DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

TECHNICAL DRAWINGS



FEATURES

Article Code: Colour: Installation: Environment: DIMENSIONS	AF81105 Silver Ceiling Indoor	Series:	Indoor
Length: Width: Height:	cm 44.8 cm 4.5 cm 9		
INCLUDED SOURCES	1.50		20001/
Category: Number:	LED 1	Color temperature (K):	3000K
Watt:	33W		
Type:	0		
Class:	Α		
LUMINAIRE			
Watt:	36W	Delivered lumens output (lm): 2256lm	

CCT:

Efficiency:

Efficacy: CRI:

Notes

Screen and CV SELV driver supplied separately.

3000K

71% 62.68lm/W



ACCESSORIES



Screen 4x Black AF95204



Screen 4x White AF95201

NO IMAGE AVAILABLE

Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of S 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses.

AF06000