
Indoor

4000K



PRODUCT DATA SHEET

Sharp SMD - 33W 54° 4000K Dimmable DALI Black



IP20 ♠ C€ Dimmerable: +①-

DESIGN BY

Carlotta de Bevilacqua


DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

Series:

Color temperature (K):

TECHNICAL DRAWINGS



FEATURES

AF82504 **Article Code:** Colour: Black Installation: Ceiling Indoor **Environment:**

DIMENSIONS

Length: cm 44.8 Width: cm 4.5 cm 9 Height:

LED

INCLUDED SOURCES

Category: Number: 33W Watt: 0 Type: Class: Α

LUMINAIRE

Watt: 36W Delivered lumens output (lm): 2501lm 4000K CCT:

Efficiency: 73% 69.47lm/W Efficacy: CRI: 90 **Dimmable Typology:** Dali

Notes

Screen and CV SELV driver supplied separately.



ACCESSORIES



Screen 4x Black AF95204



Screen 4x White AF95201

NO IMAGE AVAILABLE

Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of S 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses.
AF06000