



Sharp SMD - 3W 17° 3000K White



ΙΡ20 🝈 🕻 ε

TECHNICAL DRAWINGS



DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

FEATURES			
Article Code: Colour: Installation: Environment:	AF31301 White Ceiling Indoor	Series:	Indoor
DIMENSIONS			
Length: Width: Height:	cm 4.1 cm 4.5 cm 9		
INCLUDED SOURCES			
Category: Number: Watt: Type: Class:	LED 1 3W 0 A	Color temperature (K):	3000K
LUMINAIRE			
Watt:	3W	Delivered lumens output (lm) CCT: CRI:	: 201lm 3000K >90
Notos			

Notes

Screen and CV SELV driver supplied separately.



ACCESSORIES



Undimmable DV1032

Screen 4x Black

AF95204



Screen 1x Wh AF95001



Screen 1x Black AF95004



AF95201



Driver CV 75W 24Vdc Selv - 220-240 Vac -180x52x30 (LxWxH) - up to 65W -Undimmable DV1009



Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of S 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses. AF06000



Driver CV 120W 24Vdc Selv - 220-240 Vac -153x41x32 (LxWxH) - up to 100W -Undimmable DV1033