


PRODUCT DATA SHEET

# Sharp SMD - 44W 34° 3000K Dimmable DALI Black



IP20 💮 🕻 Dimmerable: +①-

#### **TECHNICAL DRAWINGS**



## **DESIGN BY**

Carlotta de Bevilacqua

### DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

FEATURES			
Article Code: Colour: Installation: Environment:	AF87104 Black Ceiling Indoor	Series:	Indoor
DIMENSIONS			
Length: Width: Height:	cm 59.6 cm 4.5 cm 9		
INCLUDED SOURCE	S		
Category: Number: Watt: Type: Class:	LED 1 44W 0 A	Color temperature (K):	3000К
LUMINAIRE			
Watt:	48W	Delivered lumens output ( CCT: Efficiency: Efficacy: CRI: Dimmable Typology:	( <b>Im):</b> 3009lm 3000K 71% 62.68lm/W 90 Dali
Notes			

#### Notes

Screen and CV SELV driver supplied separately.



#### ACCESSORIES



AF95204





Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of S 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses. AF06000