


PRODUCT DATA SHEET

## Sharp SMD - 44W 54° 3000K Silver



IP20 💮 ce

## **TECHNICAL DRAWINGS**



D	ESI	GN	BY
_			

Carlotta de Bevilacqua

## DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

Article Code:	AF86205	Series:	Indoor
Colour:	Silver		
nstallation:	Ceiling		
Environment:	Indoor		
DIMENSIONS			
ength:	cm 59.6		
Width:	cm 4.5		
Height:	cm 9		
INCLUDED SOURCE	S		
Category:	LED	Color temperature (K):	3000K
Number:	1		
Vatt:	44W		
Гуре:	0		
Class:	А		
LUMINAIRE			
Watt:	48W	Delivered lumens output (lm): 3116lm	
		CCT:	3000K
		Efficiency:	73%
		Efficacy:	64.91lm/W
		CRI:	90
Notes			

Screen and CV SELV driver supplied separately.



## ACCESSORIES



AF95204





Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of S 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses. AF06000