Indoor

3000K



PRODUCT DATA SHEET

Sharp SMD - 5,5W 17° 3000K Silver



IP20 ⟨ () €

DESIGN BY

Carlotta de Bevilacqua


DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

Series:

Color temperature (K):

TECHNICAL DRAWINGS



FEATURES

Article Code:	AF36305
Colour:	Silver
Installation:	Ceiling
Environment:	Indoor

DIMENSIONS

 Length:
 cm 7.8

 Width:
 cm 4.5

 Height:
 cm 9

INCLUDED SOURCES

Category.	LED
Number:	1
Watt:	5,5V
Type:	0
Class:	Α

LUMINAIRE

Watt:	5,5W	Delivered lumens output (lm): 402lm	
		CCT:	3000K
		CDI	>00

Notes

Screen and CV SELV driver supplied separately.



PRODUCT DATA SHEET

ACCESSORIES

NO IMAGE AVAILABLE

Driver CV 30W 24Vdc Selv - 220-240 Vac -153x41x32 (LxWxH) - up to 25W -Undimmable DV1032



Screen 2x White AF95101



Screen 2x Black AF95104



Screen 4x Black AF95204



Screen 4x White AF95201

NO IMAGE AVAILABLE

Driver CV 75W 24Vdc Selv - 220-240 Vac -180x52x30 (LxWxH) - up to 65W -Undimmable DV1009

NO IMAGE AVAILABLE

Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of S 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses.

AF06000

NO IMAGE AVAILABLE

Driver CV 120W 24Vdc Selv - 220-240 Vac -153x41x32 (LxWxH) - up to 100W -Undimmable DV1033