2700K



# PRODUCT DATA SHEET

# Sharp SMD - 5,5W 54° 2700K Silver



**IP**20 ⟨ ( ) €


#### **DESIGN BY**

Carlotta de Bevilacqua

#### **DESCRIPTION**

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

## **TECHNICAL DRAWINGS**



## **FEATURES**

Article Code:	AF36205	Series:	Indoor
Colour:	Silver		
Installation:	Ceiling		
Environment:	Indoor		

#### **DIMENSIONS**

 Length:
 cm 7.8

 Width:
 cm 4.5

 Height:
 cm 9

## **INCLUDED SOURCES**

Category:	LED	Color temperature (K):
Number:	1	
Watt:	5,5W	
Туре:	0	
Class:	Α	

## **LUMINAIRE**

 Watt:
 5,5W
 Delivered lumens output (Im): 366Im

 CCT:
 2700K

 CRI:
 >90

## **Notes**

Screen and CV SELV driver supplied separately.



## PRODUCT DATA SHEET

## **ACCESSORIES**

NO IMAGE AVAILABLE

Driver CV 30W 24Vdc Selv - 220-240 Vac -153x41x32 (LxWxH) - up to 25W -Undimmable DV1032



Screen 2x White AF95101



Screen 2x Black AF95104



Screen 4x Black AF95204



Screen 4x White AF95201

NO IMAGE AVAILABLE

Driver CV 75W 24Vdc Selv - 220-240 Vac -180x52x30 (LxWxH) - up to 65W -Undimmable DV1009

NO IMAGE AVAILABLE

Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of S 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses.

AF06000

NO IMAGE AVAILABLE

Driver CV 120W 24Vdc Selv - 220-240 Vac -153x41x32 (LxWxH) - up to 100W -Undimmable DV1033