

# Tagora Ceiling 80 - Led 36° 4000K - Beige/White - Dimmable Dali



IP20   Dimmerable: 


## DESIGN BY

S./R. Cornelissen

## DESCRIPTION

Series of ceiling mounted luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. □Aluminium body available in different two-coloured versions: beige/white, grey/white, black/orange, black/vert and black/blue. □Tagora 80 and 270 offer a high-output spot light with aluminium optics. □Tagora 270 uses a proprietary system based□on a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions. □Tagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use high-output sources. □Integrated electronic power supply, dimmable or non-dimmable options, depending on the version. Only ceiling mounted installation allowed.□Compliant with standard EN60598-1 and other specific standards.

## TECHNICAL DRAWINGS



## FEATURES

|                      |             |                  |           |
|----------------------|-------------|------------------|-----------|
| <b>Article Code:</b> | AB08452     | <b>Material:</b> | Aluminium |
| <b>Colour:</b>       | Beige/White | <b>Series:</b>   | Indoor    |
| <b>Installation:</b> | Ceiling     |                  |           |

## DIMENSIONS

|                |        |                        |         |
|----------------|--------|------------------------|---------|
| <b>Height:</b> | cm 33  | <b>Cutout shape:</b>   | Rounded |
| <b>Weight:</b> | kg 1.1 | <b>Glow Wire Test:</b> | 960     |

## INCLUDED SOURCES

|                  |     |                               |                 |
|------------------|-----|-------------------------------|-----------------|
| <b>Category:</b> | LED | <b>Color temperature (K):</b> | 4000K           |
| <b>Number:</b>   | 1   | <b>Color Tolerance:</b>       | MacAdam 3SDCM   |
| <b>Watt:</b>     | 14W | <b>CRI:</b>                   | 90              |
| <b>Type:</b>     | 0   | <b>Service Life:</b>          | L70 (6K) 60000h |
| <b>Class:</b>    | A   |                               |                 |

## LUMINAIRE

|                                  |  |                                      |           |
|----------------------------------|--|--------------------------------------|-----------|
| <b>Power Supply:</b>             | 220/240Vac 50/60Hz electronic ballast included | <b>Delivered lumens output (lm):</b> | 1059lm    |
| <b>Transformer availability:</b> | Integrated                                     | <b>CCT:</b>                          | 4000K     |
| <b>Watt:</b>                     | 14W  | <b>Efficiency:</b>                   | 69%       |
| <b>Voltage:</b>                  | 220V-240V                                      | <b>Efficacy:</b>                     | 75.66lm/W |
|                                  |  | <b>CRI:</b>                          | 90        |
|                                  |  | <b>Dimmable Typology:</b>            | Dali      |