PRODUCT DATA SHEET PRODUCT CODE: AB08252

# Tagora Ceiling 80 - Led 44° 3000K - Beige/White - Dimmable Dali



IP20 ⊕ ▼ Dimmerable: +①-

#### **DESIGN BY**

S./R. Cornelissen


## **DESCRIPTION**

Series of ceiling mounted luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. 

\[
\textsuperscript{\textsuperscript{Aluminium body available in different two-coloured versions: beige/white, grey/white, black/orange, black/vert and black/blue. 

\[
\textsuperscript{\textsuperscript{Tagora 80 and 270 offer a high-output spot light with aluminium optics. 
\textsuperscript{Tagora 270 uses a proprietary system based \textsuperscript{on a hybrid combined lens and reflector optic. 
\textsuperscript{This system helps to create defined narrow beams using high-powered LED modules of large dimensions. 
\textsuperscript{Tagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. 
\textsuperscript{LED versions use high-output sources. 
\textsuperscript{Integrated electronic power supply, dimmable or non-dimmable options, depending on the version. 
\textsuperscript{Only ceiling mounted installation allowed.} 
\textsuperscript{Compliant with standard EN60598-1 and other specific standards.} 
\]

## **TECHNICAL DRAWINGS**



#### **FEATURES**

Article Code: Colour: Installation: DIMENSIONS	AB08252 Beige/White Ceiling	Material: Series:	Aluminium Indoor
Height: Weight: INCLUDED SOURCES	cm 33	Cutout shape:	Rounded
	kg 1.1	Glow Wire Test:	960
Category:	LED	Color temperature (K):	3000K
Number:	1	Color Tolerance:	MacAdam 3SDCM

CRI:

Service Life:

# LUMINAIRE

Watt:

Type: Class:

Power Supply:	220/240Vac 50/60Hz	OHz <b>Delivered lumens output (lm):</b> 1110lm		
	electronic ballast	CCT:	3000K	
	included	Efficiency:	75%	
Trasformer availability:	Integrated	Efficacy:	79.34lm/W	
Watt:	14W	CRI:	90	
Voltage:	220V-240V	Dimmable Typology:	Dali	

14W

0

Α

L70 (6K) 60000h