
## Tagora Ceiling 80 - Led 52° 4000K - Black/Green - Dimmable Dali



## **TECHNICAL DRAWINGS**



## **DESIGN BY**

S./R. Cornelissen

## DESCRIPTION

Series of ceiling mounted luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. DAluminium body available in different two-coloured versions: beige/white, grey/white, black/orange, black/vert and black/blue. Dagora 80 and 270 offer a high-output spot light with aluminium optics. Dagora 270 uses a proprietary system based Don a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions. Dagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use high-output sources. DIntegrated electronic power supply, dimmable or non-dimmable options, depending on the version. Only ceiling mounted installation allowed. Compliant with standard EN60598-1 and other specific standards.

| FEATURES   |                                   |   |   |
|--|-----------------------------------|---|---|
| Article Code:<br>Colour:<br>Installation:        | AB08659<br>Black/Green<br>Ceiling | Material:<br>Series:  | Aluminium<br>Indoor                             |
| DIMENSIONS                                       |                                   |   |   |
| Height:<br>Weight:                               | cm 33<br>kg 1.1                   | Cutout shape:<br>Glow Wire Test:                                    | Rounded<br>960                                  |
| INCLUDED SOURCES                                 |                                   |   |   |
| Category:<br>Number:<br>Watt:<br>Type:<br>Class: | LED<br>1<br>14W<br>0<br>A         | Color temperature (K):<br>Color Tolerance:<br>CRI:<br>Service Life: | 4000K<br>MacAdam 3SDCM<br>90<br>L70 (6K) 60000h |
| LUMINAIRE  |                                   |   |   |
| Power Supply:                                    | electronic ballast<br>included    | Delivered lumens output (lm<br>CCT:<br>Efficiency:                  | 4000K<br>68%                                    |
| Trasformer availability:<br>Watt:<br>Voltage:    | Integrated<br>14W<br>220V-240V    | Efficacy:<br>CRI:<br>Dimmable Typology:                             | 74.78lm/W<br>90<br>Dali                         |