


## Tagora Recessed 970 -LED 3000K-Dali-SwitchDim-Orange



**TECHNICAL DRAWINGS** 



## **DESIGN BY**

S./R. Cornelissen

## DESCRIPTION

Series of ceiling mounted luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. II Consists of a trimless recessed frame fitted into the ceiling and an optical unit with an aluminium body painted in a range of colours: beige/white, grey/white, black/orange, black/vert and black/blue. II Tagora 80 and 270 offer a high-output spot light with aluminium optics. II Tagora 270 uses a proprietary system based on a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions. II Tagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use high-output sources. IIntegrated electronic power supply, dimmable or non-dimmable options, depending on the version. Only ceiling recessed installation allowed. ICompliant with standard EN60598-1 and other specific standards.

| FEATURES   |  |   |   |
|--|--|---|---|
| Article Code:<br>Colour:<br>Installation:        | M250011<br>Orange<br>Recessed                        | Material:<br>Series:  | Aluminium<br>Indoor                             |
| DIMENSIONS                                       |  |   |   |
| Weight:<br>Recessed depth:                       | kg 21<br>cm 22.7                                     | Cutout diameter:<br>Cutout shape:<br>Glow Wire Test:                | cm 100.2<br>Rounded<br>650                      |
| INCLUDED SOURCES                                 |  |   |   |
| Category:<br>Number:<br>Watt:<br>Type:<br>Class: | LED<br>1<br>84W<br>0<br>A                            | Color temperature (K):<br>Color Tolerance:<br>CRI:<br>Service Life: | 3000K<br>MacAdam 3SDCM<br>80<br>L70 (6K) 50000h |
| LUMINAIRE  |  |   |   |
| Power Supply:                                    | 220/240Vac 50/60Hz<br>electronic ballast<br>included | Delivered lumens output (lm<br>CCT:<br>Efficacy:                    | <b>1):</b> 6425lm<br>3000K<br>53.05lm/W         |
| Watt:<br>Voltage:                                | 84W<br>220V-240V                                     | CRI:<br>Dimmable Typology:  | 80<br>Dali                                      |