PRODUCT DATA SHEET PRODUCT CODE: AB04152

Tagora Suspension 80 - Led 36° 3000K - Beige/White - Dimmable Dali



IP20 ⊕ ▼ Dimmerable: +①-


DESIGN BY

S./R. Cornelissen

DESCRIPTION

Series of suspended luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. \(\text{DAluminium body available in different two-coloured versions: beige/white, grey/white, black/orange, black/vert and black/blue. \(\text{DSteel suspension cables allowing quick adjustment, 2 metre length. } \text{DTagora 80 and 270 offer a high-output spot light with aluminium optics. } \(\text{DTagora 270 uses a proprietary system based} \text{Don a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions. } \(\text{DTagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use highoutput sources. } \(\text{DIntegrated electronic power supply, dimmable or non-dimmable options, depending on the version. } \(\text{DCompliant with standard EN60598-1 and other specific standards.} \)

TECHNICAL DRAWINGS



FEATURES

Article Code:	AB04152	Material:	Aluminium
Colour:	Beige/White	Series:	Indoor
Installation:	Suspension		

DIMENSIONS

neigiit.	CIII 33
Weight:	kg 1.1
Base Diameter:	cm 10
Max Height from ceiling:	cm 200

INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K
Number:	1	Color Tolerance:	MacAdam 3SDCM
Watt:	14W	CRI:	90
Type:	0	Service Life:	L70 (6K) 60000h
Class:	Α		

Glow Wire Test:

Dimmable Typology:

960

Dali

LUMINAIRE

Voltage:

Power Supply:	220/240Vac 50/60Hz	220/240Vac 50/60Hz Delivered lumens output (lm): 1027lm		
	electronic ballast	сст:	3000K	
	included	Efficiency:	69%	
Trasformer availability:	Integrated	Efficacy:	73.39lm/W	
Watt:	14W	CRI:	90	

220V-240V