


## Tagora Suspension 80 - Led 44° 3000K - Black/Orange - Dimmable Dali



## **TECHNICAL DRAWINGS**



## **DESIGN BY**

S./R. Cornelissen

## DESCRIPTION

Watt:

Voltage:

Series of suspended luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. DAluminium body available in different twocoloured versions: beige/white, grey/white, black/orange, black/vert and black/blue. []Steel suspension cables allowing quick adjustment, 2 metre length. DTagora 80 and 270 offer a high-output spot light with aluminium optics. ITagora 270 uses a proprietary system based I on a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions. DTagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use highoutput sources. Integrated electronic power supply, dimmable or non-dimmable options, depending on the version. Compliant with standard EN60598-1 and other specific standards.

| FEATURES                                                         |                                                     |                                                                     |                                                 |
|------------------------------------------------------------------|-----------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------|
| Article Code:<br>Colour:<br>Installation:                        | AB04257<br>Black/Orange<br>Suspension               | Material:<br>Series:                                                | Aluminium<br>Indoor                             |
| DIMENSIONS                                                       |                                                     |                                                                     |                                                 |
| Height:<br>Weight:<br>Base Diameter:<br>Max Height from ceiling: | cm 33<br>kg 1.1<br>cm 10<br>cm 200                  | Glow Wire Test:                                                     | 960                                             |
| INCLUDED SOURCES                                                 |                                                     |                                                                     |                                                 |
| Category:<br>Number:<br>Watt:<br>Type:<br>Class:                 | LED<br>1<br>14W<br>0<br>A                           | Color temperature (K):<br>Color Tolerance:<br>CRI:<br>Service Life: | 3000K<br>MacAdam 3SDCM<br>90<br>L70 (6K) 60000h |
| LUMINAIRE                                                        |                                                     |                                                                     |                                                 |
| Power Supply:                                                    | 220/240Vac 50/60H<br>electronic ballast<br>included | Z Delivered lumens output (<br>CCT:<br>Efficiency:                  | ( <b>lm):</b> 1110lm<br>3000K<br>75%            |
| Trasformer availability:                                         | Integrated                                          | Efficacy:                                                           | 79.34lm/W                                       |

CRI:

**Dimmable Typology:** 

14W

220V-240V

90

Dali