PRODUCT DATA SHEET

# Tagora Suspension 970 - Direct Emission - dimmable - Grey/White



## IP40 ⊕ ▼ Dimmerable: +①-

#### **DESIGN BY**

S./R. Cornelissen

### **DESCRIPTION**

Series of suspended luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. 

Aluminium body available in different two-coloured versions: beige/white, grey/white, black/orange, black/vert and black/blue. 

Steel suspension cables allowing quick adjustment, 2 metre length. 

Tagora 80 and 270 offer a high-output spot light with aluminium optics. 

Tagora 270 uses a proprietary system based on a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions. 


Tagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use highoutput sources. 

Integrated electronic power supply, dimmable or non-dimmable options, depending on the version. 

Compliant with standard EN60598-1 and other specific standards.

PRODUCT CODE: M248961

## **TECHNICAL DRAWINGS**



### **FEATURES**

| Article Code: | M248961    | Material: | Aluminium |
|---------------|------------|-----------|-----------|
| Colour:       | Grey/White | Series:   | Indoor    |
| Installation: | Suspension |           |           |

#### **DIMENSIONS**

| Height: | cm 23 | Glow Wire Test: | 960° |
|---------|-------|-----------------|------|
| Weight: | kg 21 |                 |      |

## **INCLUDED SOURCES**

| Category: | LED | Color temperature (K): | 4000K           |
|-----------|-----|------------------------|-----------------|
| Number:   | 1   | Color Tolerance:       | MacAdam 3SDCM   |
| Watt:     | 84W | CRI:                   | 80              |
| Туре:     | 0   | Service Life:          | L70 (6K) 50000h |
| Class:    | Α   |                        |                 |

## **LUMINAIRE**

| Power Supply: | 220/240Vac 50/60Hz Delivered lumens output (lm):6915lm |             |            |
|---------------|--|-------------|------------|
|               | electronic ballast                                     | CCT:        | 4000K      |
|               | included   | Efficiency: | 54%        |
| Watt          | Q./\\/   | Efficacy    | 56.76lm/\/ |

 Watt:
 84W
 Efficacy:
 56.76lm/W

 Voltage:
 220V-240V
 CRI:
 80

 Dimmable Typology:
 Dali