


Talo sospensione LED 120 - Silver

DESIGN BY

Neil Poulton



TECHNICAL DRAWINGS



FEATURES			
Article Code:	1923020A	Material:	Aluminium,
Colour:	Silver		methacrylate,
Installation:	Suspension		polycarbonate
Environment:	Indoor	Series:	Design
		Area contract:	Hospitality, null, Retail, Office
		Emission:	Indirect Flood/direc Dark Light
DIMENSIONS			
Length:	cm 120	Glow Wire Test:	650
Width:	cm 7		
Height:	cm 100		
Base Length:	cm 49		
babe rengen.	CIII +J		
Max Height from ceiling:	cm 160		
Max Height from ceiling:			
Max Height from ceiling:		Color temperature (K):	3000K
Max Height from ceiling: INCLUDED SOURCES Category:	cm 160	Color temperature (K): Color Tolerance:	3000K MacAdam 3SDCM
Max Height from ceiling: INCLUDED SOURCES Category: Number:	cm 160	•	
Max Height from ceiling: INCLUDED SOURCES Category: Number: Watt:	cm 160 LED 7 6.72W	Color Tolerance:	MacAdam 3SDCM
Max Height from ceiling: INCLUDED SOURCES Category: Number: Watt: Delivered lumens output (l	cm 160 LED 7 6.72W	Color Tolerance: CRI:	MacAdam 3SDCM 80
Max Height from ceiling: INCLUDED SOURCES Category: Number: Watt: Delivered lumens output (I Type:	LED 7 6.72W m): 1014lm	Color Tolerance: CRI: Efficacy:	MacAdam 3SDCM 80 151lm/W
Max Height from ceiling: INCLUDED SOURCES Category: Number: Watt: Delivered lumens output (I Type: Class:	cm 160 LED 7 6.72W m):1014Im 0	Color Tolerance: CRI: Efficacy:	MacAdam 3SDCM 80 151lm/W
Max Height from ceiling: INCLUDED SOURCES Category: Number: Watt: Delivered lumens output (I Type: Class: LUMINAIRE	cm 160 LED 7 6.72W m):1014Im 0	Color Tolerance: CRI: Efficacy:	MacAdam 3SDCM 80 151lm/W 50000-L70
Max Height from ceiling: INCLUDED SOURCES Category: Number: Watt: Delivered lumens output (I Type: Class: LUMINAIRE Watt:	cm 160 LED 7 6.72W m):1014lm 0 A	Color Tolerance: CRI: Efficacy: Service Life:	MacAdam 3SDCM 80 1511m/W 50000-L70
Max Height from ceiling: INCLUDED SOURCES Category: Number: Watt: Delivered lumens output (I Type: Class: LUMINAIRE Watt:	cm 160 LED 7 6.72W m):1014lm 0 A 51W	Color Tolerance: CRI: Efficacy: Service Life: Delivered lumens output (MacAdam 3SDCM 80 1511m/W 50000-L70
0	cm 160 LED 7 6.72W m):1014lm 0 A 51W	Color Tolerance: CRI: Efficacy: Service Life: Delivered lumens output (CCT:	MacAdam 3SDCM 80 1511m/W 50000-L70 Im):5772Im 3000K

Notes

Lamp included. Available mono or double tube (on the same line), in different lengths according to the power of the light source. The suspension cables are also feed cables.