

### **PRODUCT CODE: 1921020A**


# Talo sospensione LED 90 - Silver

## **DESIGN BY**

Neil Poulton



## **TECHNICAL DRAWINGS**



Article Code:	1921020A	Material:	Aluminium,
Colour:	Silver		methacrylate,
Installation:	Suspension		polycarbonate
Environment:	Indoor	Series:	Design
		Area contract:	Hospitality, null, Retail, Office
		Emission:	Indirect Flood/direct Dark Light
DIMENSIONS			
Length:	cm 90	Glow Wire Test:	650
Width:	cm 7		
Height:	cm 100		
Base Length:	cm 49		
Max Height from ceiling:	cm 160		
INCLUDED SOURCES			
Category:	LED	Color temperature (K):	3000K
	_	Color Tolerance:	MacAdam 3SDCM
Number:	5	Color Tolerance:	
	5 6W	Color Tolerance: CRI:	80
Watt:	6W		
Watt: Delivered lumens output (l	6W	CRI:	80
Watt: Delivered lumens output (l Type:	6W <b>m):</b> 909lm	CRI: Efficacy:	80 152lm/W
Watt: Delivered lumens output (l Type: Class:	6W <b>m):</b> 909lm 0	CRI: Efficacy:	80 152lm/W
Watt: Delivered lumens output (l Type: Class: LUMINAIRE	6W <b>m):</b> 909lm 0	CRI: Efficacy:	80 152lm/W 50000-L70
Watt: Delivered lumens output (l Type: Class: LUMINAIRE Watt:	6W <b>m):</b> 909lm 0 A	CRI: Efficacy: Service Life:	80 152lm/W 50000-L70
Watt: Delivered lumens output (l Type: Class: LUMINAIRE Watt:	6W <b>m):</b> 909lm 0 A 32W	CRI: Efficacy: Service Life: Delivered lumens output (	80 152lm/W 50000-L70 ( <b>Im):</b> 3707lm
Number: Watt: Delivered lumens output (I Type: Class: LUMINAIRE Watt: Voltage:	6W <b>m):</b> 909lm 0 A 32W	CRI: Efficacy: Service Life: Delivered lumens output ( CCT:	80 152lm/W 50000-L70 (Im):3707lm 3000K

### Notes

Lamp included. Available mono or double tube (on the same line), in different lengths according to the power of the light source. The suspension cables are also feed cables.