

Vector Magnetic 55 - 26W 22° 2700K DALI Brushed copper



IP20 💮 🐺 Dimmerable: + 🕦 –


DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

Two sizes with three different beam angles each (spot, flood, wide flood) obtained by means of refractive or hybrid optical units. Junction arm integrated in the spotlight's body to keep the barycentre aligned with the track and prevent any imbalance in possible suspension versions of the track. The junction allows 360° rotation and 90° tilting for maximum emission adjustment freedom.

TECHNICAL DRAWINGS



FEATURES

| Article Code: | AP11218 | Series: | Indoor, 2018 |
|---------------|------------------|---------|---------------------|
| Colour: | Brushed copper | | Artemide Collection |
| Installation: | Track, Projector | | |
| Environment: | Indoor | | |

DIMENSIONS

| Height: | cm 15.5 |
|--------------|---------|
| Weight: | kg 0.5 |
| Base Length: | cm 24.8 |
| Inclination: | -90+90 |
| Rotation: | cm 360 |

INCLUDED SOURCES

| Category: | LED | Color temperature (K): | 2700K |
|-----------|-----|------------------------|-----------------|
| Number: | 1 | Color Tolerance: | MacAdam 3SDCM |
| Watt: | 26W | CRI: | 90 |
| Туре: | 0 | Service Life: | L70 (6K) 50000h |

IIMINIAIDE

| LUMINAIRE | | | |
|-----------|-----|--------------------------------------|-----------|
| Watt: | 26W | Delivered lumens output (lm): 1408lm | |
| | | сст: | 2700K |
| | | Efficiency: | 62% |
| | | Efficacy: | 54.16lm/W |
| | | CRI: | 90 |
| | | Dimmable Typology: | Dali |

Notes

For operarion use only Artemide Power Supply kit.



ACCESSORIES



Accessories holder
- Vector 55
AP91100



Anti-dazzle louvre - Vector 55 AP91400



Lens for elliptical emission - Vector 55 AP91200



Adjustable dowsers - Vector 55 AP91500



Soft filter - Vector 55 AP91300