Vector Magnetic 55 - 26W 32° 2700K DALI Brushed copper



IP20 🕼 🌃 Dimmerable: + 🕦 -


DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

Two sizes with three different beam angles each (spot, flood, wide flood) obtained by means of refractive or hybrid optical units. Junction arm integrated in the spotlight's body to keep the barycentre aligned with the track and prevent any imbalance in possible suspension versions of the track. The junction allows 360° rotation and 90° tilting for maximum emission adjustment freedom.

TECHNICAL DRAWINGS



FEATURES

Article Code:	AP11318 Series:	Indoor, 2018
Colour:	Brushed copper	Artemide Collection
Installation:	Projector, Track	
Environment:	Indoor	

DIMENSIONS

 Height:
 cm 15.5

 Base Length:
 cm 24.8

 Inclination:
 -90+90

 Rotation:
 cm 360

INCLUDED SOURCES

Category:	LED	Color temperature (K):	2700K
Number:	1	Color Tolerance:	MacAdam 3SDCM
Watt:	26W	CRI:	90
Type:	0	Service Life:	L70 (6K) 50000h

LUMINAIRE

Watt:	26W	Delivered lumens output (lm): 1534lm	
		сст:	2700K
		Efficiency:	68%
		Efficacy:	59.00lm/W
		CRI:	90
		Dimmable Typology:	Dali

Notes

For operarion use only Artemide Power Supply kit.



ACCESSORIES



Accessories holder
- Vector 55
AP91100



Anti-dazzle louvre - Vector 55 AP91400



Lens for elliptical emission - Vector 55 AP91200



Adjustable dowsers - Vector 55 AP91500



Soft filter - Vector 55 AP91300