


Vector Pendant Magnetic 55 - 26W 16° 4000K DALI Brushed copper



TECHNICAL DRAWINGS



DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

Two sizes with three different beam angles each (spot, flood, wide flood) obtained by means of refractive or hybrid optical units. Junction arm integrated in the spotlight's body to keep the barycentre aligned with the track and prevent any imbalance in possible suspension versions of the track. The junction allows 360° rotation and 90° tilting for maximum emission adjustment freedom.

| Article Code: | AP35118 | Series: | Indoor, 2018 |
|--------------------------|----------------|-----------------------------------|-----------------------------|
| Colour: | Brushed copper | | Artemide Collection |
| Installation: | Projector, | | |
| | Suspension | | |
| Environment: | Indoor | | |
| DIMENSIONS | | | |
| Height: | cm 13 | | |
| Base Length: | cm 24.8 | | |
| Inclination: | -90+90 | | |
| Rotation: | cm 360 | | |
| Max Height from ceiling: | cm 200 | | |
| INCLUDED SOURCES | | | |
| Category: | LED | Color temperature (K): | 4000K |
| Number: | 1 | CRI: | 90 |
| Watt: | 26W | | |
| | 0 | | |
| Туре: | 0 | | |
| Type: LUMINAIRE | 0 | | |
| | 26W | Delivered lumens output (| lm): 1492lm |
| LUMINAIRE | | Delivered lumens output (CCT: | lm): 1492lm 4000K |
| LUMINAIRE | | - | |

Notes

For operarion use only Artemide Power Supply kit.