

Vector Recessed 55 - 17,5W 16° 4000K Brushed Copper



IP20 (ii)


DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

Two sizes with three different beam angles each (spot, flood, wide flood) obtained by means of refractive or hybrid optical units. The junction allows 360° rotation and 90° tilting for maximum emission adjustment freedom. Vector 40 and 55 available version: recessed trim or trimless.

TECHNICAL DRAWINGS



FEATURES

| Article Code: Colour: Installation: Environment: | AP56118 Brushed Copper Projector, Recessed Indoor | Material: Series: | Alluminium body Indoor, 2018 Artemide Collection |
|--|--|----------------------|--|
| DIMENSIONS | | | |

| Height: | cm 13.6 | Cutout diameter: | cm 8.6 |
|--------------|---------|------------------|--------|
| Inclination: | -90+90 | | |
| Rotation: | cm 360 | | |

INCLUDED SOURCES

| Category: | LED | Color temperature (K): | 4000K |
|-----------|-------|------------------------|-----------------|
| Number: | 1 | Color Tolerance: | MacAdam 3SDCM |
| Watt: | 17,5W | CRI: | 90 |
| Туре: | 0 | Service Life: | L70 (6K) 50000h |
| | | | |

| Watt: | 17,5W | Delivered lumens oเ | itput (lm): 1268lm |
|-------|-------|---------------------|--------------------|
| | | CCT: | 4000K |
| | | Efficiency: | 64% |
| | | Efficacy: | 74.57lm/W |
| | | CRI: | 90 |

Trimless recessed structure not included, to be ordered separately. Driver 700/500mA SELV supplied separately. Depending on the driver, the product can be dimmable DALI or undimmable.



ACCESSORIES







Vector 55 -Optional Trim Frame Ø 108 -Black Ap59104



Driver 11-25W 500-700mA - 220-24Vac - Dimmable DALI -164x38x24,5 mm (LxWxH) dv1031



Vector 40 -Trimless recessed structure AP50000



Vector 55 -Optional Trim Frame Ø 108 -White Ap59101