


# Vector Track 40 10W 13° 4000K Undimmable Brushed Bronze



IP20 🗆

## TECHNICAL DRAWINGS



### **DESIGN BY**

Carlotta de Bevilacqua

#### DESCRIPTION

Three sizes with three different beam angles each (spot, flood, wide flood) obtained by means of refractive or hybrid optical units. Vector 55 track DALI zoom optic (22°-32°). Junction arm integrated in the spotlight's body to keep the barycentre aligned with the track and prevent any imbalance in possible suspension versions of the track. The junction allows 360° rotation and 90° tilting for maximum emission adjustment freedom. Vector 95 available only in track version. Version with compact 4-conductor (3p+n) adapter with hidden LED driver and not-dimmable phase selector.

| FEATURES  |   |  |  |
|---|---|--|--|
| Article Code:<br>Colour:<br>Installation:<br>Environment: | AN05120<br>Brushed Bronze<br>Projector, Track<br>Indoor | Series:  | Indoor, 2018<br>Artemide Collection        |
| DIMENSIONS  |   |  |  |
| Height:<br>Base Length:<br>Inclination:<br>Rotation:      | cm 15.4<br>cm 22.8<br>-90+90<br>cm 360                  |  |  |
| INCLUDED SOURCES  |   |  |  |
| Category:<br>Number:<br>Watt:<br>Type:<br>Class:          | LED<br>1<br>10W<br>0<br>A                               | Color temperature (K):<br>Color Tolerance:<br>Service Life:              | 4000K<br>MacAdam 3SDCM<br>L70 (6K) 50000h  |
| LUMINAIRE   |   |  |  |
| Watt:   | 10W   | Delivered lumens output (lm)<br>CCT:<br>Efficiency:<br>Efficacy:<br>CRI: | : 540lm<br>4000K<br>81%<br>54.09lm/W<br>90 |
| Notes   |   |  |  |

220/240Vac 50/60Hz Electronic ballast included.



## PRODUCT CODE: AN05120

#### ACCESSORIES



- Vector 40 AP90100



Anti-dazzle louvre - Vector 40 AP90400



emission - Ve 40 AP90200



Soft filter - Vector 40 AP90300