

**BEGA****22 663**

Ceiling and wall luminaire



Project · Reference number

Date



## Product data sheet

### Application

Unshielded LED ceiling and wall luminaire with high protection class.

A luminaire made of die cast aluminium and with an impact resistant crystal glass.

### Product description

Luminaire made of aluminium alloy, aluminium and stainless steel  
 Crystal glass, white inside  
 2 mounting holes  $\varnothing$  4.3 mm  
 Distance apart 115 mm  
 2 cable entries for through-wiring of mains supply cable  $\varnothing$  7-10.5 mm  
 Connecting terminal and earth conductor terminal 2.5<sup>□</sup>  
 LED power supply unit  
 220-240 V  $\sim$  0/50-60 Hz  
 DC 176-264 V  
 Safety class I  
 Protection class IP 65  
 Dust-tight and protection against water jets  
 Impact strength IK05  
 Protection against mechanical impacts < 0.7 joule  
 – Safety mark  
 – Conformity mark  
 Weight: 1.3 kg

### Inrush current

Inrush current: 7 A / 112  $\mu$ s  
 Maximum number of luminaires of this type per miniature circuit breaker:  
 B 10A: 38 luminaires  
 B 16A: 61 luminaires  
 C 10A: 64 luminaires  
 C 16A: 102 luminaires

### Lamp


Module connected wattage	2.9 W
Luminaire connected wattage	4 W
Rated temperature	$t_a = 25$ °C
Ambient temperature	$t_{a \max} = 50$ °C

### 22 663 K3

Module designation	LED-0280/930
Colour temperature	3000 K
Colour rendering index	CRI > 90
Module luminous flux	465 lm
Luminaire luminous flux	226 lm
Luminaire luminous efficiency	56,5 lm/W

### 22 663 K4

Module designation	LED-0280/940
Colour temperature	4000 K
Colour rendering index	CRI > 90
Module luminous flux	480 lm
Luminaire luminous flux	233 lm
Luminaire luminous efficiency	58,2 lm/W



### Service life · Ambient temperature

Ambient temperature $t_a = 25$ °C	
LED psu:	> 50,000 h
LED module:	> 200,000 h (L 80 B 50) 100,000 h (L 90 B 50)

Ambient temperature $t_a = 50$ °C	
LED psu:	50,000 h
LED module:	> 200,000 h (L 80 B 50) 100,000 h (L 90 B 50)

### Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page [www.bega.com](http://www.bega.com).

### Article No. 22 663

LED colour temperature optionally 3000 K or 4000 K  
 3000 K – Article number + **K3**  
 4000 K – Article number + **K4**

### Light distribution

