

BEGA**22 751**

Ceiling and wall luminaire



Project · Reference number

Date


Product data sheet

Application

Unshielded LED ceiling and wall luminaire with high protection class.

A luminaire made of die cast aluminium and with an impact resistant crystal glass.

Product description

Luminaire made of aluminium alloy, aluminium and stainless steel
 Crystal glass, white inside
 2 mounting holes \varnothing 5.5 mm
 Distance apart 89 mm
 2 cable entries for through-wiring of mains supply cable \varnothing 7-10.5 mm
 Connection terminal 2.5²
 Earth conductor connection
 LED power supply unit
 220-240 V \sim 0/50-60 Hz
 DC 176-264 V
 Safety class I
 Protection class IP 65
 Dust-tight and protection against water jets
 Impact strength IK06
 Protection against mechanical impacts < 1 joule
 – Safety mark
CE – Conformity mark
 Weight: 2.8 kg

Inrush current

Inrush current: 11 A / 112 μ s
 Maximum number of luminaires of this type per miniature circuit breaker:
 B10A: 34 luminaires
 B16A: 55 luminaires
 C10A: 57 luminaires
 C16A: 92 luminaires

Lamp


Module connected wattage	6.6 W
Luminaire connected wattage	7.7 W
Rated temperature	$t_a = 25$ °C
Ambient temperature	$t_{a \max} = 50$ °C

22 751 K3

Module designation	LED-0262/930
Colour temperature	3000 K
Colour rendering index	CRI > 90
Module luminous flux	1115 lm
Luminaire luminous flux	551 lm
Luminaire luminous efficiency	71,6 lm/W

22 751 K4

Module designation	LED-0262/940
Colour temperature	4000 K
Colour rendering index	CRI > 90
Module luminous flux	1180 lm
Luminaire luminous flux	583 lm
Luminaire luminous efficiency	75,7 lm/W



Service life · Ambient temperature

Ambient temperature $t_a = 25$ °C	
LED psu:	> 50,000 h
LED module:	> 200,000 h (L80 B50) 100,000 h (L90 B50)

Ambient temperature $t_a = 50$ °C	
LED psu:	50,000 h
LED module:	> 200,000 h (L80 B50) 100,000 h (L90 B50)

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Article No. 22 751

LED colour temperature optionally 3000 K or 4000 K
 3000 K – Article number + **K3**
 4000 K – Article number + **K4**

Colour graphite or silver
 graphite – article number
 silver – article number + **A**

Light distribution

