

BEGA**24 073**

Ceiling and wall luminaire



Project · Reference number


Date

Product data sheet

Application

Ceiling and wall luminaire.
Luminaire for lighting and surface design.
Installed as wall luminaire the luminaire can be used horizontally or vertically.
For interior and exterior applications.

Product description

Luminaire made of aluminium alloy, aluminium and stainless steel
White synthetic diffuser
2 mounting holes \varnothing 7 mm
Distance apart 900 mm
2 cable entries for through-wiring of mains supply cable \varnothing 7-10,5 mm, max. 3 G 1.5[□]
Connecting terminal 2.5[□]
Earth conductor connection
Lampholder G 13
Electronic ballast (EEI=A2)
220-240 V \sim 0/50-60 Hz
DC 167-264 V
DC Start \geq 198 V
Safety class I
Protection class IP 44
Protected against granular foreign bodies > 1 mm and splash water
Impact strength IK04
Protection against mechanical impacts < 0.5 joule
 – Safety mark
CE – Conformity mark
Weight: 4.0 kg

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Lamps

2 Fluorescent lamps
T 26 · 36 W · G 13
Osram: Lumilux T8 L 36 W 3350 lm
Philips: Master TL-D 36 W 3350 lm

Please note the lamp manufacturers' operating instructions.

