BEGA 24377

Plug & Play Spherical luminaires



Project · Reference number

Date

Product data sheet

Application

BEGA Plug & Play

Portable LED spherical luminaires 48 V DC consisting of 3 luminaires with hook.

Product description

Housing and hook made of glass fibre reinforced synthetic material

White synthetic diffuser with screw neck Silicone gasket

With 5 m cable between the 48 V plug and the first luminaire

Cable length between the luminaires 2 m Safety class III ��

Protection class IP 65

Dust-tight and protection against water jets

Impact strength IK10 Protection against mechanical

impacts < 20 joule

CE – Conformity mark

Weight: 1.1 kg

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Lamp


On request we can offer you modifications for environments with higher temperatures as a customized product.

Voltage 48 V = DC

24 377 K3

Module designation LED-0835/830
Colour temperature 3000 K
Colour rendering index CRI > 80
Module luminous flux 1950 Im
Luminaire luminous flux 1623 Im
Luminaire luminous efficiency 138,7 Im/W





Service life \cdot Ambient temperature

Rated temperature $t_a = 25 \, ^{\circ}\text{C}$ LED psu: > 50,000 h

LED module: 167,000h (L80B50)

Ambient temperature $t_{a \text{ max}}$ = 45 °C (100 %)

LED psu: 50,000h

LED module: 50,000 h (L80 B50) 76,000 h (L70 B50)

Accessories

13566 Smart Tower with connecting cable

and mains plug

13567 Smart Tower with connecting cable

and free cable end

13568 Smart Extender

Distributor with 5 m cable and 48V

plug, switchable and dimmable via

Zigbee Conrol module 10596 Extension cable 5 m

10596 Extension cable 5 m 10597 Extension cable 10 m 10526 Remote control ONE

13569 Remote control PRO **70588** Gateway

for controlling your lighting system by app BEGA Gateway from a smartphone or tablet

For the accessories a separate instructions for use can be provided upon request.