BEGA 24 379

# Plug & Play Spherical luminaires



Project · Reference number

Date

## Product data sheet

#### **Application**

BEGA Plug & Play

Portable LED spherical luminaires 48 V DC consisting of 5 luminaires with earth spike.

#### **Product description**

Housing and earth spike made of glass-fibre reinforced polyamide

White synthetic diffuser with screw neck Silicone gasket

With 5 m cable between the 48 V plug and the

first luminaire
Cable length between the luminaires 2 m

Cable length between the luminaires 2 n Safety class III �

Protection class IP 65

Dust-tight and protection against water jets Impact strength IK10

Protection against mechanical

impacts < 20 joule

C € – Conformity mark

Weight: 1.9 kg

#### Light technique


Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

### Lamp

### 24 379 K3

Module designation	LED-0835/830
Colour temperature	3000 K
Colour rendering index	CRI > 80
Module luminous flux	3100 lm
Luminaire luminous flux	2580 lm
Luminaire luminous efficiency	131 6 lm/W





## Service life of the LED

Ambient temperature  $t_a$  = 25 °C – at 287,000 h: L70 B50

max. ambient temperature  $t_a$ = 50 °C – at 68,000 h: L70 B50

#### Accessories

**13 566** Smart Tower with connecting cable

and mains plug

**13567** Smart Tower with connecting cable

and free cable end

13568 Smart Extender

Distributor with 5 m cable and 48V

plug, switchable and dimmable via

Zigbee Conrol module

**10 596** Extension cable 5 m **10 597** Extension cable 10 m

10 597 Extension cable 10 m10 526 Remote control ONE

13569 Remote control PRO

**70 588** Gateway

for controlling your lighting system by app BEGA Gateway from a smartphone or tablet

For the accessories a separate instructions for use can be provided upon request.