## BEGA

Plug & Play Spherical luminaires

Project · Reference number

### Product data sheet

#### Application

BEGA Plug & Play Portable LED spherical luminaires 48 V DC consisting of 5 luminaires with hook.

#### Product description

Housing and hook made of glass fibre reinforced synthetic material White synthetic diffuser with screw neck Silicone gasket With 5 m cable between the 48 V plug and the first luminaire Cable length between the luminaires 2 m Safety class III ♠ Protection class IP 65 Dust-tight and protection against water jets Impact strength IK10 Protection against mechanical impacts < 20 joule C€ – Conformity mark Weight: 1.9 kg

## Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

#### Lamp

Module connected wattage	5x 3.3 W
Luminaire connected wattage	19.6 W
Rated temperature	t <sub>a</sub> =25 °C
Ambient temperature	$t_{a max} = 45 \ ^{\circ}C$

On request we can offer you modifications for enviroments with higher temperatures as a customized product. Voltage 48 V = DC

#### 24 380 K3

Module designation	LED-0835/830
Colour temperature	3000 K
Colour rendering index	CRI > 80
Module luminous flux	3100 lm
Luminaire luminous flux	2580 lm
Luminaire luminous efficiency	131,6 lm/W

ccc

# 

#### Service life of the LED

Ambient temperature  $t_a = 25 \text{ °C}$ - at 236,000 h: L70 B50

max. ambient temperature  $t_a$  = 45 °C – at 75,000 h: L70 B50

#### Accessories

13 566	Smart Tower with connecting cable
	and mains plug
13 567	Smart Tower with connecting cable
	and free cable end
13 568	Smart Extender
	Distributor with 5 m cable and 48V
	plug, switchable and dimmable via
	Zigbee Conrol module
10 596	Extension cable 5 m
10 597	Extension cable 10 m
10 526	Remote control ONE
13 569	Remote control PRO
70 588	Gateway
	for controlling your lighting system
	by app BEGA Gateway from a
	smartphone or tablet

For the accessories a separate instructions for use can be provided upon request.

# Date

**24 380** <sup>⊕</sup> IP 65