

**BEGA****31 410**

Wall luminaire



Project · Reference number

Date

## Product data sheet

### Application

Wall luminaire for many lighting tasks on or in buildings.

A luminaire with antique glass diffuser for brilliant light.

### Product description

Luminaire made of aluminium alloy,

aluminium and stainless steel

BEGA Unidure® coating technology

Antique glass

2 mounting holes  $\varnothing$  5.2 mm

Distance apart 70 mm

1 cable entry for mains supply cable

up to  $\varnothing$  10,5 mm max.  $3 \times 1,5$

Connecting terminal 2.5

with plug connection

Earth conductor connection


Lampholder E 27

Safety class I

Protection class IP 23

Protected against granular foreign bodies

> 12 mm and showers up to 60°

 – Safety mark

 – Conformity mark

Weight: 3.0 kg

### Lamp

Luminaire with lampholder E 27

Lamp output max. 100 W

For this luminaire we recommend the following BEGA LED lamps:

**13509** LED 7 W · 805 lm · 2700 K

**13547** LED 7 W · 805 lm · 2700 K  
dimmmable

**13583** LED 7 W · 805 lm · 3000 K

**13585** LED 7 W · 805 lm · 3000 K  
dimmmable

**13511** LED 8 W · 1055 lm · 2700 K

**13562** LED 12 W · 1520 lm · 2700 K

**13563** LED 12 W · 1520 lm · 2700 K  
dimmmable

**13587** LED 8 W · 1055 lm · 3000 K

**13589** LED 12 W · 1520 lm · 3000 K

**13591** LED 12 W · 1520 lm · 3000 K  
dimmmable

Detailed technical and lighting data for the lamps can be found in the data sheets on our website.

