

BEGA**31 428**

Wall luminaire



Project · Reference number


Date

Product data sheet

Application

Wall luminaire with crystal bubble glass.
For many lighting tasks in or on buildings.

Product description

Luminaire made of aluminium alloy
and stainless steel
BEGA Unidure® coating technology
Antique glass
2 mounting holes \varnothing 5.2 mm
Distance apart 70 mm
1 cable entry for mains supply cable
up to \varnothing 10,5 mm max. $3 \times 1,5^{\square}$
Connecting terminal 2.5[□]
with plug connection
Earth conductor connection
Lampholder E 27
Safety class I
Protection class IP 44
Protected against granular foreign bodies
> 1 mm and splash water
 – Safety mark
CE – Conformity mark
Weight: 3.5 kg

Lamp

Luminaire with lampholder E 27
Lamp output max. 100 W

For this luminaire we recommend the following
BEGA LED lamps:

13 509 LED 7 W · 805 lm · 2700 K

13 547 LED 7 W · 805 lm · 2700 K
dimnable

13 583 LED 7 W · 805 lm · 3000 K

13 585 LED 7 W · 805 lm · 3000 K
dimnable

13 511 LED 8 W · 1055 lm · 2700 K

13 562 LED 12 W · 1520 lm · 2700 K

13 563 LED 12 W · 1520 lm · 2700 K
dimnable

13 587 LED 8 W · 1055 lm · 3000 K

13 589 LED 12 W · 1520 lm · 3000 K

13 591 LED 12 W · 1520 lm · 3000 K
dimnable

Detailed technical and lighting data for the
lamps can be found in the data sheets on our
website.

