

Project · Reference number

Date

Product data sheet

Application

Luminaire for installation on pillars, walls or parapets for interior and exterior applications.
Luminaire with hand-blown crystal bubble glass for brilliant light.

Product description

Luminaire made of aluminium alloy,
aluminium and stainless steel
BEGA Unidure® coating technology
Antique glass
Mounting plate with 3 fixing holes $\varnothing$ 8.5 mm
Angle 120° · Pitch circle $\varnothing$ 100 mm
Mounting bracket with 2-pole terminal block 4[□]
and earth conductor terminal for connection of
mains supply cable max. 3 × 2.5[□]
Lampholder E 27
Safety class I
Protection class IP 44
Protected against granular foreign bodies
> 1 mm and splash water
CE – Conformity mark
Weight: 4.6 kg

Lamp

Luminaire with lampholder E 27
Lamp output max. 100 W

For this luminaire we recommend the following
BEGA LED lamps:

13509 LED 7 W · 805 lm · 2700 K

13547 LED 7 W · 805 lm · 2700 K
dimable

13583 LED 7 W · 805 lm · 3000 K

13585 LED 7 W · 805 lm · 3000 K
dimable

13511 LED 8 W · 1055 lm · 2700 K

13562 LED 12 W · 1520 lm · 2700 K

13563 LED 12 W · 1520 lm · 2700 K
dimable

13587 LED 8 W · 1055 lm · 3000 K

13589 LED 12 W · 1520 lm · 3000 K

13591 LED 12 W · 1520 lm · 3000 K
dimable

Detailed technical and lighting data for the
lamps can be found in the data sheets on our
website.

