

BEGA**33 185**

Lichtbaustein®



Project · Reference number

Date


Product data sheet

Application

Lichtbaustein®

Ceiling and wall luminaire for many lighting tasks.
Ideal for places where a soft and uniform lighting distribution is required.
For interior and exterior applications.

Product description

Luminaire made of aluminium alloy and stainless steel
BEGA Unidure® coating technology
Opal glass
2 mounting holes \varnothing 5 mm
Distance apart 160 mm
2 cable entries for through-wiring of mains supply cable \varnothing 7-10.5 mm
Lampholder terminal 2.5²
Earth conductor connection
Lampholder E 27
Safety class I
Protection class IP 44
Protected against granular foreign bodies > 1 mm and splash water
Impact strength IK02
Protection against mechanical impacts < 0.2 joule
 – Safety mark
CE – Conformity mark
Weight: 0.85 kg

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Lamp

Luminaire with lampholder E 27
Lamp output max. 40 W

For this luminaire we recommend the following BEGA LED lamps:



13510 LED 7 W · 805 lm · 2700 K

13548 LED 7 W · 805 lm · 2700 K
dimmable

13584 LED 7 W · 805 lm · 3000 K

13586 LED 7 W · 805 lm · 3000 K
dimmable

Detailed technical and lighting data for the lamps can be found in the data sheets on our website.



Light distribution

