

BEGA**33 563**

Lichtbaustein ®



Project · Reference number

Date

Product data sheet

Application

Lichtbaustein® Rectangle
Ceiling and wall luminaire for many lighting tasks.
Ideal for places where a soft and uniform
lighting distribution is required.
For interior and exterior applications.

Product description

Luminaire made of aluminium alloy
and stainless steel
Opal glass satin matt
1 fixing hole \varnothing 7 mm
1 cable entry for mains supply cable
up to \varnothing 10,5 mm max. $3 \times 1,5^{\square}$
Lampholder terminal 2.5^{\square}
Earth conductor connection
Lampholder E 14
Safety class I
Protection class IP 44
Protected against granular foreign bodies
> 1 mm and splash water
Impact strength IK03
Protection against mechanical
impacts < 0.35 joule
 – Safety mark
CE – Conformity mark
Weight: 0.75 kg

Lamp

Luminaire with lampholder E 14
Lamp output max. 40 W

For this luminaire we recommend the following
BEGA LED lamps:



13 552 LED 4 W · 470 lm · 2700 K

13 554 LED 5 W · 470 lm · 2700 K
dimmmable

13 594 LED 4 W · 470 lm · 3000 K

13 596 LED 5 W · 470 lm · 3000 K
dimmmable

Detailed technical and lighting data for the
lamps can be found in the data sheets on our
website.



Light technique

Luminaire data for the light planning program
DIALux for outdoor lighting, street lighting and
indoor lighting as well as luminaire data in
EULUMDAT- and IES-format you will find on the
BEGA web page www.bega.com.

Light distribution

