

BEGA**44 344**

Ceiling and wall luminaire



Project · Reference number


Date

Product data sheet

Application

Ceiling and wall luminaire.
Luminaire for lighting and surface design.
Installed as wall luminaire the luminaire can be used horizontally or vertically.
For interior and exterior applications.

Product description

Luminaire made of aluminium alloy, aluminium and stainless steel
White synthetic diffuser
2 fixing holes \varnothing 6 mm
480 mm spacing
2 cable entries for through-wiring of mains supply cable \varnothing 7-10,5 mm, max. 3G1.5[□]
3-pole plug connection with connecting terminal and earth conductor terminal 2.5[□]
Lampholder G 13
Electronic ballasts (EEL=A2)
220-240 V \sim 0/50-60 Hz
DC 176-276 V
DC Start \geq 198 V
Safety class I
Protection class IP 44
Protected against granular foreign bodies > 1 mm and splash water
Impact strength IK05
Protection against mechanical impacts < 0.7 joule
 – Safety mark
CE – Conformity mark
Weight: 1.6 kg

Lamp

Fluorescent lamp
T 26 · 18 W · G 13

Osram: LUMILUX T8 L 18 W 1350 lm
Philips: Master TL-D 18 W 1350 lm

Please note the lamp manufacturers' operating instructions.

