

BEGA**44 668**

Ceiling · Wall · Pillar luminaire



Project · Reference number



Date

Product data sheet

Application

Unshielded luminaire for installation under ceilings, on walls as well as on pillars and murals. By means of the three-ply opal glass the light is distributed softly and uniformly over the glass surface.

Product description

Luminaire made of aluminium alloy, aluminium and stainless steel
 BEGA Unidure® coating technology
 Opal glass with screw neck
 2 mounting holes \varnothing 4.5 mm
 Distance apart 50 mm
 2 cable entries for through-wiring of mains supply cable \varnothing 7-10.5 mm
 Connection terminal 2.5²
 Earth conductor connection
 Lampholder E 27
 Safety class I
 Protection class IP 65
 Dust-tight and protection against water jets
 Impact strength IK06
 Protection against mechanical impacts < 1 joule
 – Safety mark
 – Conformity mark
 Weight: 1.9 kg

Lamp

Luminaire with lampholder E 27
 Lamp output max. 75 W

For this luminaire we recommend the following BEGA LED lamps:

13 510 LED 7 W · 805 lm · 2700 K

13 548 LED 7 W · 805 lm · 2700 K
 dimmable

13 584 LED 7 W · 805 lm · 3000 K

13 586 LED 7 W · 805 lm · 3000 K
 dimmable

13 512 LED 8 W · 1055 lm · 2700 K

13 588 LED 8 W · 1055 lm · 3000 K

Radio-controlled version (Zigbee 3.0):

13 555 LED 9 W · 805 lm · 2700 K
 dimmable

13 556 LED 9 W · 805 lm · 2700-6500 K
 dimmable · tunable white

13 557 LED 9.5 W · 805 lm · 2700-6500 K
 dimmable · tunable white · RGBW

Detailed technical and lighting data for the lamps can be found in the data sheets on our website.

