

**BEGA****50016 P**

Ceiling and wall luminaire for indoor use



Project · Reference number


Date

## Product data sheet

### Application

Ceiling and wall luminaire · indoor luminaire made of impact resistant synthetic diffuser and metal housing, for all lighting tasks. They are ideal for places where a soft and uniform lighting distribution is required.

### Product description

Metal housing,  
finish white enamel  
Impact resistant synthetic diffuser, white,  
with bayonet closure  
2 mounting holes  $\varnothing$  6 mm  
Distance apart 340 mm  
2 cable entries for through-wiring for mains  
cable up to  $\varnothing$  10,5 mm max.  $3 \times 1,5^{\square}$   
Connection terminal 2.5 $^{\square}$   
Earth conductor connection  
LED power supply unit  
220-240 V  $\sim$  0/50-60 Hz  
DC 170-280 V  
Safety class I  
 – Safety mark  
**CE** – Conformity mark

### Inrush current

Inrush current: 20 A / 400  $\mu$ s  
Maximum number of luminaires of this  
type per miniature circuit breaker:  
B 10A: 9 luminaires  
B 16A: 15 luminaires  
C 10A: 15 luminaires  
C 16A: 25 luminaires

### Lamp

Module connected wattage 43.5 W  
Luminaire connected wattage 48.7 W  
Rated temperature  $t_a = 25$  °C  
Ambient temperature  $t_{a \max} = 30$  °C

### 50016 P K3


Colour temperature 3000 K  
Colour rendering index CRI > 90  
Module luminous flux 5505 lm  
Luminaire luminous flux 4149 lm  
Luminaire luminous efficiency 85,2 lm/W

### 50016 P K2

Colour temperature 2700 K  
Colour rendering index CRI > 90  
Module luminous flux 5465 lm  
Luminaire luminous flux 4118 lm  
Luminaire luminous efficiency 84,6 lm/W

### 50016 P K4

Colour temperature 4000 K  
Colour rendering index CRI > 90  
Module luminous flux 5705 lm  
Luminaire luminous flux 4299 lm  
Luminaire luminous efficiency 88,3 lm/W



### Service life of the LED

Ambient temperature  $t_a = 25$  °C  
– at 139,000h: L70B50  
max. ambient temperature  $t_a = 30$  °C  
– at 105,000h: L70B50

### Light technique

Luminaire data for the light planning program  
DIALux for outdoor lighting, street lighting and  
indoor lighting as well as luminaire data in  
EULUMDAT- and IES-format you will find on the  
BEGA web page [www.bega.com](http://www.bega.com).

### Article No. 50016 P

LED colour temperature optionally 2700 K,  
3000 K or 4000 K  
2700 K – Article number + **K2**  
3000 K – Article number + **K3**  
4000 K – Article number + **K4**

### Accessory · Trim rings

For this luminaire metal trim rings in 3 enamel  
surfaces are optional available.  
Trim rings are accessories and must be ordered  
separately.

Item	Part. No
Finish enamel <b>white</b>	<b>13007</b>
Finish enamel <b>palladium</b>	<b>13008</b>
Finish enamel <b>glossy silver</b>	<b>13009</b>